

WAC LIGHTING

1" LEDme

Square Open Reflector Downlight w/ Integral Driver

Fixture Type: _____
Catalog Number: _____
Project: _____
Location: _____

Model	Color Temp & CRI	Lumens	CBCP	Finish
HR-LED251E	27 2700K - 85	245	530	BN Brushed Nickel
	30 3000K - 85	250	540	GM Gun Metal
	35 3500K - 85	270	573	WT White
	40 4000K - 85	285	608	

Example: **HR-LED251E-27-BN**

DESCRIPTION


Perfect for ceilings, under cabinet and wall niches. LED Miniature Recessed Downlights offer a super low profile and Die-cast aluminum trim with a 25° cutoff angle for comfortable general and task lighting.

FEATURES


- New Construction, may be re-configured in the field for Remodel
- Driver required
- 5 year warranty

SPECIFICATIONS

Construction	Die-cast aluminum trim, aluminum heat sink and 20 gauge steel housing painted black.
Power:	4W
Input:	120 VAC, 50/60Hz
Dimming:	ELV: 100-10%
Light Source:	Integrated LED, 3 Step Mac Adam Ellipse
Rated Life:	80,000 Hours
Mounting:	Heavy gauge retention clips secures housing firmly to ceiling
Cut Out:	2 1/2"
Finish:	Electrostatically Powder Coated: White, Electroplated Gun Metal, Electroplated Brushed Nickel
Ceiling Thickness:	1/2" - 1"
Operating Temp:	-4°F to 104°F (-20°C to 40°C)
Standards:	UL, cUL, Damp Location Listed, IC



FINISHES:



Brushed Nickel

Gun Metal

White