

INVISILED® PRO

24V LED Tape Light

WAC



Tape Section



3 LED "L" Connector

Fixture Type:

Catalog Number:

Project:

Location:

PRODUCT DESCRIPTION

Professional grade white tape light that delivers optimal color consistency and brightness. An ideal dimmable system for task or accent lighting application in residential, hospitality and commercial environments.

FEATURES

- Can be field cut, male to male adapter required to re-use female side
- Ultra thin profile at 3/8"
- Diodes spaced evenly at 1" on center
- Minimum run length of 1'
- May be field cut every 2" at the end of a run
- Three mounting methods provided for different surfaces
- Specially rated for installation in the storage area of a clothes closet
- 50,000 hour rated life
- 5 year WAC Lighting product warranty

SPECIFICATIONS


- Construction:** Flexible silicone-cased tape light, peel-and-stick 3M construction adhesive, indicating marks on back for field cutting
- Light Source:** 12 LEDs per foot, Runs on 24V at 3W per foot
- Operating Temp:** -4°F – 122°F (-20°C – 50°C), relative humidity 95%
- Standards:** UL & cUL Listed for Damp Locations

ORDER NUMBER – TAPE SECTION

Model	Watts/ft	Color Temp	CRI	Lumens/ft	Length	Qty	Tape Color
LED-T24 3	W 2700K	85	200	2IN	2 inches	1	WT White
	P 3000K	85	200	2IN-10	2 inches	10	
	35 3500K	85	207	1	1 foot	1	
	C 4500K	85	215	1-40	1 foot	40	
				5	5 feet	1	

LED-T24___-___-**WT**

Example: **LED-T24P-2IN-10-WT**




ORDER NUMBER – 3 LED "L" CONNECTOR

Model	Watts/ft	Color Temp	CRI	Lumens/ft	Tape Color
LED-T24 1.2	W 2700K	85	50	3L-WT	White
	P 3000K	85	50		
	35 3500K	85	52		
	C 4500K	85	54		

LED-T24___-**3L-WT**

Example: **LED-T24C-3L-WT**



wacighting.com
Phone (800) 526.2588
Fax (800) 526.2585

Headquarters, East Manufacturing Facility
44 Harbor Park Drive
Port Washington, NY 11050

South East Manufacturing Facility
1600 Distribution Ct
Lithia Springs, GA 30122

Central Manufacturing Facility
1700 South J Elmer Freeway, Ste 100
Cedar Hill, TX 75104






West Manufacturing Facility
1750 S Archibald Ave
Ontario, CA 91761

INVISILED® PRO


24V LED Tape Light

WAC


Class 2 Power Supply (Required)


	Model		Input	Output	Max Run	Dimming	Description
	EN-2460-RB2-T	Remote	120VAC	24VAC / 60W	20'	100%-5% ELV	Includes a 6' lead wire. UL Class 2 output.
	EN-24100-RB2-T		120VAC	24VAC / 96W	33'		
	PS-24DC-U60R-T	Remote	120-277VAC	24VDC / 60W	20'	100%-5% ELV, TRIAC	Includes a 6' lead wire. UL Class 2 output.
	PS-24DC-U96R-T			24VDC / 96W	33'		
	EN-24100-277-RB2-T	Remote	277VAC	24VDC / 96W	33'	100%-5% 0-10V	Includes a 6' lead wire. UL Class 2 output.
	EN-2460-P-AR-T	Plug-in	120VAC	24VAC / 60W	20'	Non Dimmable	Includes a 6' lead wire. UL Class 2 output.
	EN-24100-P-AR-T		120VAC	24VAC / 96W	33'		
	EN-D24100-120-R	Wall Dimmer & Driver	120VAC	24VDC / 96W	33'	Integral	UL Class 2 output.

Indoor Controller


	Model		Description
	CT-6A-R2	Pro, Pro2, Pro3, LITE	Touch Panel and Motion Sensor Includes a Touch Panel, Occupancy Sensor and a Controller. AC/DC input at 12V(60W Max) or 24V(96W Max). Connect on secondary side of driver/transformer.
	IR-96-24VACDC-WT IR-96-24VACDC-BK	White Black	IR Sensor IR (Infrared sensor) switch works by turning the light on when it becomes unobstructed.

Smart Control

	Model	Description
	CT-96-SM	InvisILED® Smart Home Kit Transform your interiors with the InvisILED® Smart Home Kit, designed exclusively for InvisILED Lite, Pro, Pro 2 and Pro 3 Tape. Control your LED tape seamlessly via Wi-Fi using the MyWAC app with devices you already own, including Amazon Alexa and Google Home. Offers on/off activation and up/down dimming capability for 24VDC systems and high-output tape lighting applications. Or use DMX to control your popular control platforms. Includes a 96W 24VDC Power Supply (EN-24DC096-UNV-RB2), wireless controller (CTR-WDMX-24VDC) and a ready-to-connect lead wire with an InvisILED Connector (LED-TC-B-2-WT)

	Model	Input	Description
	LED-WCT-WT	120-230VAC	<ul style="list-style-type: none"> - Multi-scene selection - Raise/Lower, dedicated Off button - Suitable for standard single NEMA wall box Setup and configuration via MyWAC mobile application - no physical adjustment needed - cUL listed

EXAMPLE INSTALLATION FOR WIRELESS AND DMX CONTROL



wacighting.com
Phone (800) 526.2588
Fax (800) 526.2585

Headquarters, East Manufacturing Facility
44 Harbor Park Drive
Port Washington, NY 11050

South East Manufacturing Facility
1600 Distribution Ct
Lithia Springs, GA 30122

Central Manufacturing Facility
1700 South J Elmer Freeway, Ste 100
Cedar Hill, TX 75104

West Manufacturing Facility
1750 S Archibald Ave
Ontario, CA 91761

INVISILED® PRO

24V LED Tape Light

WAC

Indoor Electrical Accessories

	Model	Dimension	Finish	Description
	LED-TC-WEXT-144	12 ft	Black	In Wall Rated Extension Cable Extends distance between a hard wired power supply or a wiring box to a tape section.
	LED-TC-WEXT-144-WT	12 ft	White	
	LED-TC-WEXT-240	20 ft	Black	
	LED-TC-WEXT-240-WT	20 ft	White	
	LED-TC-WIC-144	12 ft	Black	In Wall Rated Joiner Cable Connects tape sections. 2 female ends. 1 male to male connector included.
	LED-TC-WIC-144-WT	12 ft	White	
	LED-TC-WIC-240	20 ft	Black	
	LED-TC-WIC-240-WT	20 ft	White	
	LED-TC-P-2	2 ft	Black	Lead Wire Alternative lengths for plug-in power supplies.
	LED-TC-P-2-WT	2 ft	White	
	LED-TC-P-12	12 ft	Black	
	LED-TC-P-12-WT	12 ft	White	
	LED-TC-EXT-144	12 ft	Black	Extension Cable Extends distance between a hard wired power supply or a wiring box to a tape section.
	LED-TC-EXT-144-WT	12 ft	White	
	LED-TC-B-2	L: 1½ in W: ¾ in H: ⅞ in	Black	Low Voltage Wiring Box With Feed Neatly houses connections for up to two wires with 12" female feed.
	LED-TC-B-2-WT		White	
	LED-T-B	L: 1½ in W: ¾ in H: ⅞ in	White	Low Voltage Wiring Box Neatly houses connections for up to two wires.
	TB-S	L: 6¼ in W: 1½ in H: 1¼ in	White	Wiring Box With Switch Use when spanning a large gap in a system layout without leaving exposed wiring. Optional switch included.

Compatible with Pro, Pro2, Pro3

	Model	Dimension	Finish	Description
	LED-TC-IC2	2 in	Black	Joiner Cable Connects tape sections.
	LED-TC-IC2-WT	2 in	White	
	LED-TC-IC6	6 in	Black	
	LED-TC-IC6-WT	6 in	White	
	LED-TC-IC12	12 in	Black	
	LED-TC-IC12-WT	12 in	White	
	LED-TC-IC36	36 in	Black	
	LED-TC-IC36-WT	36 in	White	
	LED-TC-IC72	72 in	Black	
	LED-TC-IC72-WT	72 in	White	






LED-TC-MM

50 Qty

Black

Connector
Male to male connector.

Compatible with Pro, Pro2, Pro3, LITE. Change directionality of tape runs and reuse cut ends of tape.

	Model	Finish	Description
	LED-TC-Y	Black	3-Way "Y" Connector Connects tape sections.
	LED-TC-Y-WT	White	
	LED-TC-X	Black	4-Way "X" Connector Connects tape sections.
	LED-TC-X-WT	White	
	LED-TC-L	Black	"L" Connector Connects tape sections.
	LED-TC-L-WT	White	
	LED-TC-EC	Black	End Cap 1 cut and 1 male end cap.
	LED-TC-EC-WT	White	

Compatible with Pro, Pro2, Pro3, LITE.

	Model	Dimension	Finish	Description
	T24-OD-SW60	5 ft	Black	DMX Joiner Cable - Satellite Connect between CTR-WDMX-24VDC Master to Satellite
	T24-OD-SW120	10 ft		
	T24-OD-MW60	5 ft	Black	DMX Joiner Cable Connect between DMX Universe to CTR-WDMX-24VDC
	T24-OD-MW120	10 ft		

wacighting.com
Phone (800) 526.2588
Fax (800) 526.2585

Headquarters, East Manufacturing Facility
44 Harbor Park Drive
Port Washington, NY 11050

South East Manufacturing Facility
1600 Distribution Ct
Lithia Springs, GA 30122

Central Manufacturing Facility
1700 South J Elmer Freeway, Ste 100
Cedar Hill, TX 75104

West Manufacturing Facility
1750 S Archibald Ave
Ontario, CA 91761

INVISILED® PRO

Indoor Aluminum Channels

WAC



Aluminum Channel
Additional End Caps

LED-T-CH 5 feet
LED-T-CH-EC 2 pcs

*Diffuses light from InvisILED® tape
Includes a diffuser, two end caps, and five screws*



45° Angled Aluminum Channel
Additional End Caps

LED-T-CH2 5 feet
LED-T-CH2-EC 2 pcs

Includes a diffuser, two end caps, and five screws



Deep Aluminum Channel -
Spot 9° Beam Angle.
Additional End Caps

LED-T-CH3-SP 5 feet
LED-T-CH1-EC 2 pcs

Eliminates visible hot spots / 9° beam angles



Deep Aluminum Channel
Additional End Caps

LED-T-CH1 5 feet
LED-T-CH1-EC 2 pcs

*Eliminates visible hot spots
Includes a diffuser, two end caps, and five screws*



Deep Aluminum Channel -
Flood 54° Beam Angle
Additional End Caps

LED-T-CH3-FL 5 feet
LED-T-CH1-EC 2 pcs


Eliminates visible hot spots / 54° beam angles



Deep Aluminum Channel -
Wide Flood 84° Beam Angle
Additional End Caps


LED-T-CH3-WF 5 feet
LED-T-CH1-EC 2 pcs

Eliminates visible hot spots / 84° beam angles



Fixed Angle Channel Clip **LED-T-CL3-PT**

Includes 2 pieces, 4 screws. Use to mount Aluminum Channel.



Adjustable Channel Clip **LED-T-CL2-PT**

*Includes 2 pieces, 4 screws. Used to mount Aluminum Channel.
Adjusts 50° from center either way.*

INDOOR MOUNTING ACCESSORIES



Aluminum Retrofit Channel **LED-T-RC** 3 feet

Can be bent to create fixed curves or used as a glare shield



Clip **LED-T-CL** **Curve Clip** **LED-T-CL1**

*For surfaces that are difficult to adhere.
Includes: 10 pcs plastic clips and 10 pcs screws.
Compatible with InvisILED LITE, PRO,
PRO2 and PRO3 only.*

*Clips to hold indoor InvisILED tapes
sections. Includes: 10 pcs plastic clips and
10 pcs screws. Compatible with InvisILED
LITE, PRO, PRO2 and PRO3 only.*

wacighting.com
Phone (800) 526.2588
Fax (800) 526.2585

Headquarters, East Manufacturing Facility
44 Harbor Park Drive
Port Washington, NY 11050

South East Manufacturing Facility
1600 Distribution Ct
Lithia Springs, GA 30122

Central Manufacturing Facility
1700 South J Elmer Freeway, Ste 100
Cedar Hill, TX 75104


West Manufacturing Facility
1750 S Archibald Ave
Ontario, CA 91761

INVISILED® PRO

Symmetrical Recessed Channel

WAC


Installs within $\frac{5}{8}$ " drywall depth
 Linear channel can be field cut
 Accommodates either one or two runs of indoor tape
 Includes a translucent white acrylic diffuser
 Dense foam insert to be removed in installation after spackling



8ft Linear Channel

LED-T-RCH1-WT

*Includes: 1 diffuser
 8 perforated metal sheets*





Power Feed

LED-T-RBOX1-WT

The end cap may be placed on either side
 Hanger bars may be installed on any side of the wiring box
 Kit includes:


- 1 wiring box
- 2 hanger bars
- 4 five-pin adapters
- 2 end caps
- 1 diffuser
- 2 channel connectors
- 1 counter sink drill bit
- 1 drill bit
- 1 installation tool



Lateral Corner

LED-T-CTC1-WT

*Includes: Diffuser
 2 channel connectors
 2 perforated metal sheets*




Perpendicular Corner

LED-T-WTC1-WT

Transitions between walls or wall to ceiling

*Includes: Diffuser
 2 channel connectors
 2 perforated metal sheets*




Outside Corner

LED-T-WTW1-WT

Transitions around columns, bump outs, or soffits

*Includes: Diffuser
 2 channel connectors
 2 perforated metal sheets*



wacighting.com
 Phone (800) 526.2588
 Fax (800) 526.2585

Headquarters, East Manufacturing Facility
 44 Harbor Park Drive
 Port Washington, NY 11050

South East Manufacturing Facility
 1600 Distribution Ct
 Lithia Springs, GA 30122

Central Manufacturing Facility
 1700 South J Elmer Freeway, Ste 100
 Cedar Hill, TX 75104

West Manufacturing Facility
 1750 S Archibald Ave
 Ontario, CA 91761

INVISILED® PRO

Asymmetrical Recessed Channel


WAC



Installs within $\frac{5}{8}$ " drywall depth
 Linear channel can be field cut
 Accommodates one run of indoor tape
 Dense foam insert to be removed in installation after spackling
 Recommended installation within 15 inches of surface to be illuminated

8ft Linear Channel **LED-T-RCH2-WT**

Includes: 8 perforated metal sheets
 2 channel connectors





Indoor tape




Power feed **LED-T-RBOX2-WT**

The end cap may be placed on either side
 Hanger bars may be installed on any side of the wiring box


Includes: 1 wiring box
 2 hanger bars
 2 five-pin adapters
 2 end caps (left and right)
 2 channel connectors
 1 counter sink bit
 1 drill bit



Indirect Recessed Channel




Linear channel can be field cut
 Accommodates up to four runs of indoor tape
 Dense foam insert to be removed in installation after spackling
 Allows option to use different color tape in one channel and switch them separately



Indoor invisILED® tape

8ft Linear Channel **LED-T-RCH3-WT**




Includes: 10 perforated metal sheets
 2 channel connectors



Power feed **LED-T-RBOX3-WT**

The end cap may be placed on either side
 Hanger bars may be installed on any side of the wiring box

Includes: 1 wiring box
 2 hanger bars
 4 five-pin adapters
 1 end cap
 2 channel connectors
 1 counter sink drill bit
 1 drill bit



wacighting.com
 Phone (800) 526.2588
 Fax (800) 526.2585

Headquarters, East Manufacturing Facility
 44 Harbor Park Drive
 Port Washington, NY 11050

South East Manufacturing Facility
 1600 Distribution Ct
 Lithia Springs, GA 30122

Central Manufacturing Facility
 1700 South J Elmer Freeway, Ste 100
 Cedar Hill, TX 75104

West Manufacturing Facility
 1750 S Archibald Ave
 Ontario, CA 91761