

WAC LIGHTING

2.5" Low Voltage

Downlight Trim

Fixture Type: _____
Catalog Number: _____
Project: _____
Location: _____

| Model & Light Source | Lumens | Finish |
|---|--------|---|
| HR-836 LED MR16 (Order separately) HR-836LED LED MR16 (Included) | | BN Brushed Nickel CB Copper Bronze WT White |

Example: **HR-836-BN**

DESCRIPTION

Superb performance delivered in a small package. The 2.5" Low Voltage Recessed Downlight series offers smooth and crisp light for under cabinet and tight recessed spaces where miniature apertures are desired. For use with HR-800 series low voltage housings. Accepts MR16 LED, housing and lamp are sold separately.

FEATURES


- Accommodates most LED MR16 lamps
- Retention clips secure lens firmly to lamp
- Clear lens included, replaceable lens options available
- 5 year warranty

SPECIFICATIONS

| | |
|------------------------|---|
| Construction | 20 gauge steel with die-cast aluminum baffle |
| Light Source: | LED MR16 (Order separately), LED MR16 (Included) |
| Finish: | Electrostatically Powder Coated: Electroplated Brushed Nickel, Electroplated Copper Bronze, White |
| Operating Temp: | -4°F to 104°F (-20°C to 40°C) |
| Standards: | UL, cUL, Damp Location Listed |



FINISHES:



WAC LIGHTING

2.5" Low Voltage

Non-IC Housing for Cabinet Use

Model

HR-800 2.5in Under Cabinet Remodel Housing

Fixture Type: _____

Catalog Number: _____

Project: _____

Location: _____

Example: **HR-800**

DESCRIPTION

Superb performance delivered in a small package. The 2.5" Low Voltage Recessed Downlight series offers smooth and crisp light for under cabinet and tight recessed spaces where miniature apertures are desired. May be used with any WAC compatible 2.5" HR-837, HR-834, or HR-836 trims.

FEATURES

- For cabinet use only
- Total depth of 4", one of the lowest profile recessed units available
- Low profile housing
- Transformer required
- 5 year warranty

SPECIFICATIONS

| | |
|---------------------------|--|
| Construction | 20 gauge steel |
| Input: | 12 VAC,50/60Hz |
| Dimming: | ELV: % |
| Light Source: | Halogen MR16 (Sold Separately) |
| Mounting: | No screws, nails or hardware required. Flat "wing" springs expand against the cut out hole to hold fixture against the surface |
| Cut Out: | 3" |
| Ceiling Thickness: | 3/4" |
| Operating Temp: | -4°F to 104°F (-20°C to 40°C) |
| Standards: | UL, cUL, Damp Location Listed, Non IC |



WAC LIGHTING

2.5" Low Voltage

Remodel Non-IC Housing Non-IC

Model & Product

HR-801 2.5in Low Voltage Remodel Non-IC Housing

Fixture Type: _____

Catalog Number: _____

Project: _____

Location: _____

Example: **HR-801**

DESCRIPTION

Superb performance delivered in a small package. The 2.5" Low Voltage Recessed Downlight series offers smooth and crisp light for under cabinet and tight recessed spaces where miniature apertures are desired. May be used with any WAC compatible 2.5" HR-837, HR-834, or HR-836 trims.

FEATURES

- Integral Electronic Transformer
- Advanced auto-reset, soft start and short circuit protection
- 3" clearance on all sides when insulation is present
- Suitable for chain wiring
- J-box and transformer accessible through ceiling opening
- Transformer included
- 5 year warranty

SPECIFICATIONS

| | |
|---------------------------|--|
| Construction | 20 gauge steel |
| Power: | 50W |
| Input: | 120 VAC,50/60Hz |
| Dimming: | ELV: 100-10% |
| Light Source: | Halogen MR16 (Sold Separately) |
| Mounting: | No screws, nails or hardware required. Flat "wing" springs expand against the cut out hole to hold fixture against the surface |
| Cut Out: | 3" |
| Ceiling Thickness: | 3/4" |
| Operating Temp: | -4°F to 104°F (-20°C to 40°C) |
| Standards: | UL, cUL, Damp Location Listed, Non IC |



WAC LIGHTING

2.5" Low Voltage

New Construction Non-IC Housing

Model & Product

HR-802 2.5in Low Voltage New Construction Non-IC Housing

Fixture Type: _____

Catalog Number: _____

Project: _____

Location: _____

Example: **HR-802**

DESCRIPTION

Superb performance delivered in a small package. The 2.5" Low Voltage Recessed Downlight series offers smooth and crisp light for under cabinet and tight recessed spaces where miniature apertures are desired. May be used with any WAC compatible 2.5" HR-837, HR-834, or HR-836 trims.

FEATURES

- 3" clearance on all sides when insulation is present
- Total depth of 4", one of the lowest profile recessed units available
- Low profile housing
- Transformer included
- 5 year warranty

SPECIFICATIONS

| | |
|---------------------------|---|
| Construction | 20 gauge steel |
| Power: | 50W |
| Input: | 120 VAC,50/60Hz |
| Dimming: | ELV: 100-10% |
| Light Source: | Halogen MR16 |
| Mounting: | Supplied with hanger bars, adjustable from 15"-242" to accommodate various joist construction and grid sizes. |
| Cut Out: | 3" |
| Ceiling Thickness: | 3/4" |
| Operating Temp: | -4°F to 104°F (-20°C to 40°C) |
| Standards: | UL, cUL, Damp Location Listed, Non IC |



WAC LIGHTING

2.5" Low Voltage

New Construction Non-IC Housing

Fixture Type: _____
 Catalog Number: _____
 Project: _____
 Location: _____

ACCESSORIES

| | <i>Model</i> | <i>Description</i> | <i>Finish</i> |
|---|--|--|-------------------------------|
|  | LENS-16-RED LENS-16-GRN LENS-16-BLU LENS-16-AMB | Colored Lens Colored Lens Colored Lens Colored Lens | Red Green Blue Amber |
|  | LENS-16-FR | Clear/Frosted Lens | Frosted |
|  | LENS-16-SPR | Spread Lens | Spread Lens |
|  | LENS-16-UVF | UV Filter lens | Clear |
|  | LENS-16-BEL | Beam Elongating Lens | Beam Elongating |
|  | LENS-16-HCL | Honeycomb Louver | Black |