

# WAC LIGHTING

## 5" Square

### Ceiling and Wall Mount

Model & Size	Color Temp & CRI	Watt	Lumens	Finish
FM-05SQ 5"	930 3000K - 90	12W	1030	BZ Bronze
	935 3500K - 90	12W	1030	NI Nickel WT White

Fixture Type: \_\_\_\_\_

Catalog Number: \_\_\_\_\_

Project: \_\_\_\_\_

Location: \_\_\_\_\_

Example: **FM-05SQ-930-BZ**

#### DESCRIPTION

Ultra-slim flush mount that uses edge-lit technology and a translucent diffuser for uniform illumination without shadows or hotspots.

#### FEATURES


- Multiple LED array for uniform illumination
- Suitable for outdoor and coastal regions
- Dead front trim for shower applications
- Driver installed within the Junction Box, driver dimension: 2.25" dia x 1" deep
- 5 year warranty

#### SPECIFICATIONS

<b>Construction</b>	Injection molded UV rated plastic with translucent diffuser for outdoor application
<b>Power:</b>	12W
<b>Input:</b>	120 VAC, 50/60Hz
<b>Dimming:</b>	ELV: 100-5% , TRIAC: 100-5%
<b>Light Source:</b>	Integrated LED
<b>Lens:</b>	Translucent acrylic diffuser
<b>Mounting:</b>	Installs over a 3", 4" or 3/0-4/0 hybrid junction box, Can be mounted on ceiling or wall in all orientations
<b>Finish:</b>	Enamel Coated Nickel, Enamel Coated Bronze, Enamel Coated White
<b>Operating Temp:</b>	-40°F to 122°F (-40°C to 50°C)
<b>Standards:</b>	ETL, cETL, Wet Location Listed, ADA, Title 24 JA8 Compliant



#### FINISHES:



#### LINE DRAWING

