

# WAC LIGHTING

## 6" 120V

### Downlight Step Baffle Trim

Model	Finish
R-620	BN Brushed Nickel WT/WT White/White

Fixture Type: \_\_\_\_\_  
Catalog Number: \_\_\_\_\_  
Project: \_\_\_\_\_  
Location: \_\_\_\_\_

Example: **R-620-BN**

#### DESCRIPTION


6" Line Voltage Recessed Downlights are available with a full suite of trim options to ensure proper lamp position with low glare and superior photometric performance. Line voltage recessed gimbal trim for adjustability. For use with R-600 series line voltage housings. Accepts PAR30, R30, or A19 medium base LED or incandescent lamp 75W max for IC-Rating, housing and lamp are sold separately. Trim includes retention clips to secure firmly into housing. Features stamped metal construction and abrasion resistant powder coat painted finish.

#### FEATURES

- Secured to lamp holder bracket by steel springs
- Provided with foam rubber gasket around outer perimeter
- Abrasion resistant powder coat paint or plated metal finish
- Handles surfaces up to 3/4"
- Utilizes LED PAR30 lamp or medium base incandescent lamps. Incandescent lamps are rated for up to 75W watts max. Lamps are ordered separately.
- 5 year warranty



#### FINISHES:



#### SPECIFICATIONS

<b>Construction</b>	Durable stamped metal construction. Secured within lamp housing by steel spring clips. Provided with foam rubber gasket around outer perimeter.
<b>Light Source:</b>	PAR30, R30 ( Order Separately )
<b>Finish:</b>	Electrostatically Powder Coated: White/White, Electroplated Brushed Nickel
<b>Ceiling Thickness:</b>	Up to 3/4"
<b>Operating Temp:</b>	-4°F to 104°F (-20°C to 40°C)
<b>Standards:</b>	UL, cUL, Damp Location Listed