

# WAC LIGHTING

## Balto II

### Flush Mount 4CCT

Fixture Type: \_\_\_\_\_  
Catalog Number: \_\_\_\_\_  
Project: \_\_\_\_\_  
Location: \_\_\_\_\_

Model & Size	Color Temp	Finish	LED Watts	LED Lumens	Delivered Lumens
FMW704605 5"	2700K/3000K/3500K/4000K	BK Black WT White	13.2W	1125	615

Example: **FMW704605S-WT**

For custom requests please contact [customs@wacighting.com](mailto:customs@wacighting.com)

#### DESCRIPTION

Minimalist design meets maximum versatility. Defined by its clean circular profile and frosted interior diffuser BALTO II blends sophistication with modern architecture. Built to endure the elements, this versatile fixture is wet rated for outdoor use.

#### FEATURES


- Built in color temperature adjustability. Switch from 2700K/3000K/3500K/4000K
- Option available for sauna application. Durable and heat resistant. Available in 3000K only (Model#FMW704605S)
- Sauna application operating temperature: Min -4 F/Max 185 F
- Weather resistant powder coated finishes
- ACLED driverless technology
- 5 year warranty




#### SPECIFICATIONS

<b>Color Temp:</b>	2700K/3000K/3500K/4000K,3000K
<b>Input:</b>	120V,50/60Hz
<b>CRI</b>	90
<b>Dimming:</b>	ELV: 100-10% , TRIAC: 100-10%
<b>Rated Life:</b>	50,000 Hours
<b>Mounting:</b>	Can be mounted on ceiling or wall in all orientations
<b>Standards:</b>	ETL, cETL, Title 24 JA8 Compliant, ADA, Wet Location Listed
<b>Construction</b>	Aluminum body with interior frosted PC diffuser

#### FINISHES:



#### LINE DRAWING



FMW704605

# WAC LIGHTING

## Balto II

### Flush Mount 4CCT

Fixture Type: \_\_\_\_\_  
Catalog Number: \_\_\_\_\_  
Project: \_\_\_\_\_  
Location: \_\_\_\_\_

Model & Size	Color Temp	Finish	LED Watts	LED Lumens	Delivered Lumens
FMW704605S 5"	3000K	BK Black WT White	3.3W	373	135

Example: **FMW704605S-WT**

For custom requests please contact [customs@wacighting.com](mailto:customs@wacighting.com)

#### DESCRIPTION

Minimalist design meets maximum versatility. Defined by its clean circular profile and frosted interior diffuser BALTO II blends sophistication with modern architecture. Built to endure the elements, this versatile fixture is wet rated for outdoor use.

#### FEATURES


- Built in color temperature adjustability. Switch from 2700K/3000K/3500K/4000K
- Option available for sauna application. Durable and heat resistant. Available in 3000K only (Model#FMW704605S)
- Sauna application operating temperature: Min -4 F/Max 185 F
- Weather resistant powder coated finishes
- ACLED driverless technology
- 5 year warranty



#### SPECIFICATIONS

<b>Color Temp:</b>	2700K/3000K/3500K/4000K,3000K
<b>Input:</b>	120V,50/60Hz
<b>CRI</b>	90
<b>Dimming:</b>	ELV: 100-10% , TRIAC: 100-10%
<b>Rated Life:</b>	50,000 Hours
<b>Mounting:</b>	Can be mounted on ceiling or wall in all orientations
<b>Standards:</b>	ETL, cETL, Title 24 JA8 Compliant, ADA, Wet Location Listed
<b>Construction</b>	Aluminum body with interior frosted PC diffuser

#### FINISHES:



#### REPLACEMENT PARTS

RPL-DIF-704605 - BALTO II REPL DIFFUSER