

WAC LIGHTING

Blaze 6" Square Remodel Downlight

Fixture Type: _____
Catalog Number: _____
Project: _____
Location: _____

| Model | Beam | Color Temp & CRI | Lumens | CBCP | Finish |
|--------|-------|---|--------|------|----------|
| R6DSDR | F 55° | 9CS 2700K/3000K/3500K/4000K/5000K - 90 | 2360 | 2340 | WT White |

Example: **R6DSDR-F9CS-WT**

DESCRIPTION

Minimum profile downlight with metal conduit and driver included for easy remodel or new construction installation.

FEATURES

- 5-CCT Switchable between 2700K and 5000K
- Sold as remodel, but new construction frame available
- Metal Conduit with Quick Connect to allow for easy installation
- Driver included
- 5 year warranty

SPECIFICATIONS

| | |
|---------------------------|--|
| Construction | Die-cast Aluminum with 20-gauge Cold Rolled Steel Driver Box |
| Power: | 25W |
| Input: | 120-277 VAC,50/60Hz |
| Dimming: | ELV: 100-10% , TRIAC: 100-5% |
| Light Source: | Integrated LED |
| Lens: | Frosted TIR lens |
| Rated Life: | 50,000 Hours |
| Mounting: | Heavy gauge retention clips secures fixture to ceiling |
| Cut Out: | 5 1/2" |
| Finish: | Electrostatically Powder Coated: White |
| Ceiling Thickness: | 1/2" - 1 1/2" |
| Operating Temp: | -4°F to 104°F (-20°C to 40°C) |
| Standards: | ETL, cETL, Wet Location Listed, Title 24 JA8 Compliant, Airtight, IC |



FINISHES:



White


WAC LIGHTING

Blaze 6" Square

Remodel Downlight

Fixture Type: _____
Catalog Number: _____
Project: _____
Location: _____

ACCESSORIES

| | <i>Model</i> | <i>Description</i> | <i>Finish</i> |
|---|--------------|--------------------|---------------|
|  | R6DRDN-FRAME | Blaze 6" | |