

WAC LIGHTING

Cylinder

Outdoor Wall Sconce

Fixture Type: _____
Catalog Number: _____
Project: _____
Location: _____

Model	Color Temp & CRI	Lumens	Finish
WS-W230301	30 3000K - 90	1085	BK Black BZ Bronze WT White

Example: **WS-W230301-30-WT**

For custom requests please contact customs@wacighting.com

DESCRIPTION

Offered in a curvaceous single and double head configuration, the adjustable Cylinder Indoor/Outdoor Sconces provide strong energy efficient LED spot lighting precisely where you need it. Cleanly finished with no visible hardware, these stylish aluminum cylinders are available in three architectural powder coat finishes.

FEATURES


- Multiple LED array for uniform illumination
- Grooved swivel joint to allow precise and secure aiming
- Driver concealed within the fixture
- 5 year warranty

SPECIFICATIONS

Color Temp:	3000K
Input:	120 VAC, 50/60Hz
CRI	90
Dimming:	ELV: 100-10%
Rated Life:	50,000 Hours
Mounting:	Installs over a 3", 4" or 3/0-4/0 hybrid junction box
Standards:	ETL, cETL, Title 24 JA8 Compliant, ADA, Wet Location Listed
Construction	Die-cast aluminum with TIR lens



FINISHES:



WAC LIGHTING

Cylinder

Outdoor Wall Sconce

Fixture Type: _____
Catalog Number: _____
Project: _____
Location: _____

Model	Color Temp & CRI	Lumens	Finish
WS-W230302	30 3000K - 90	1085 x 2	BK Black BZ Bronze WT White

Example: **WS-W230302-30-WT**

For custom requests please contact customs@wacighting.com

DESCRIPTION

Offered in a curvaceous single and double head configuration, the adjustable Cylinder Indoor/Outdoor Sconces provide strong energy efficient LED spot lighting precisely where you need it. Cleanly finished with no visible hardware, these stylish aluminum cylinders are available in three architectural powder coat finishes.

FEATURES

- Multiple LED array for uniform illumination
- Grooved swivel joint to allow precise and secure aiming
- Driver concealed within the fixture
- 5 year warranty

SPECIFICATIONS

Color Temp:	3000K
Input:	120 VAC, 50/60Hz
CRI	90
Dimming:	ELV: 100-10%
Rated Life:	50,000 Hours
Mounting:	Installs over a 3", 4" or 3/0-4/0 hybrid junction box
Standards:	ETL, cETL, Title 24 JA8 Compliant, ADA, Wet Location Listed
Construction	Die-cast aluminum with TIR lens



FINISHES:

