

WAC LIGHTING

Dot Ceiling Mount

Fixture Type: _____
Catalog Number: _____
Project: _____
Location: _____

Model & Size	Color Temp	Finish	LED Watts	LED Lumens	Delivered Lumens
FM-W57806 6"	2700K	BK Black SS Stainless Steel	10W	878	574
	3000K				
	3500K				

Example: **FM-W57806-35-SS**

For custom requests please contact customs@wacighting.com

DESCRIPTION

Optimal diffuser amplifies the rightness on this durable waterproof outdoor flush mount.

FEATURES


- Lightweight, injection-molded, UV-rated acrylic diffuser enhances brightness, safety lock prevents slippage
- 277V option available for 9", 12" & 15" sizes (special order)
- Built in color temperature adjustability. Switch from 2700K/3000K/3500K
- Compact 3CCT switch installs within the junction box
- Option to pre-select color temperature or adjust in the field
- 0-10V dimming option (LDS065M010AFE-LO1) available (special order), unit dimensions: 3.4" x 1.2" x 0.5"
- ACLED driverless technology
- 5 year warranty



SPECIFICATIONS

Color Temp:	2700K,3000K,3500K
Input:	120 VAC,50/60Hz
CRI	90
Dimming:	ELV: 100-10% , TRIAC: 100-10%
Rated Life:	50,000 Hours
Mounting:	Can be mounted on ceiling or wall in all orientations
Standards:	ETL, cETL, IP65, Title 24 JA8 Compliant, Energy Star 2.0, ADA, Wet Location Listed
Construction	Weather-resistant 316 stainless steel body with thick acrylic shade

FINISHES:




WAC LIGHTING

Dot

Ceiling Mount

Fixture Type: _____
Catalog Number: _____
Project: _____
Location: _____

LINE DRAWING:



FM-W57806

WAC LIGHTING

Dot Ceiling Mount

Fixture Type: _____
Catalog Number: _____
Project: _____
Location: _____

Model & Size	Color Temp	Finish	LED Watts	LED Lumens	Delivered Lumens
FM-W57809 9"	2700K	BK Black SS Stainless Steel	17W	1571	1070
	3000K				
	3500K				

Example: **FM-W57809F-35-BK**

•For 277V special order, add an "F" before the finish: FM-W57809F-35-SS

For custom requests please contact customs@wacighting.com

DESCRIPTION

Optimal diffuser amplifies the rightness on this durable waterproof outdoor flush mount.

FEATURES

- Lightweight, injection-molded, UV-rated acrylic diffuser enhances brightness, safety lock prevents slippage
- 277V option available for 9", 12" & 15" sizes (special order)
- Built in color temperature adjustability. Switch from 2700K/3000K/3500K
- Compact 3CCT switch installs within the junction box
- Option to pre-select color temperature or adjust in the field
- 0-10V dimming option (LDS065M010AFE-LO1) available (special order), unit dimensions: 3.4" x 1.2" x 0.5"
- ACLED driverless technology
- 5 year warranty



SPECIFICATIONS

Color Temp:	2700K,3000K,3500K
Input:	120 VAC,50/60Hz
CRI	90
Dimming:	ELV: 100-10% , TRIAC: 100-10%
Rated Life:	50,000 Hours
Mounting:	Can be mounted on ceiling or wall in all orientations
Standards:	ETL, cETL, IP65, Title 24 JA8 Compliant, Energy Star 2.0, ADA, Wet Location Listed
Construction	Weather-resistant 316 stainless steel body with thick acrylic shade

FINISHES:




WAC LIGHTING

Dot

Ceiling Mount

Fixture Type: _____
Catalog Number: _____
Project: _____
Location: _____

LINE DRAWING:



FM-W57809

WAC LIGHTING

Dot Ceiling Mount

Fixture Type: _____
Catalog Number: _____
Project: _____
Location: _____

Model & Size	Color Temp	Finish	LED Watts	LED Lumens	Delivered Lumens
FM-W57812 12"	2700K	BK Black SS Stainless Steel	27W	2566	1482
	3000K				
	3500K				

Example: **FM-W57812F-35-BK**

•For 277V special order, add an "F" before the finish: FM-W57812F-35-SS

For custom requests please contact customs@wacighting.com

DESCRIPTION

Optimal diffuser amplifies the rightness on this durable waterproof outdoor flush mount.

FEATURES

- Lightweight, injection-molded, UV-rated acrylic diffuser enhances brightness, safety lock prevents slippage
- 277V option available for 9", 12" & 15" sizes (special order)
- Built in color temperature adjustability. Switch from 2700K/3000K/3500K
- Compact 3CCT switch installs within the junction box
- Option to pre-select color temperature or adjust in the field
- 0-10V dimming option (LDS065M010AFE-LO1) available (special order), unit dimensions: 3.4" x 1.2" x 0.5"
- ACLED driverless technology
- 5 year warranty



SPECIFICATIONS

Color Temp:	2700K,3000K,3500K
Input:	120 VAC,50/60Hz
CRI	90
Dimming:	ELV: 100-10% , TRIAC: 100-10%
Rated Life:	50,000 Hours
Mounting:	Can be mounted on ceiling or wall in all orientations
Standards:	ETL, cETL, IP65, Title 24 JA8 Compliant, Energy Star 2.0, ADA, Wet Location Listed
Construction	Weather-resistant 316 stainless steel body with thick acrylic shade

FINISHES:




WAC LIGHTING

Dot

Ceiling Mount

Fixture Type: _____
Catalog Number: _____
Project: _____
Location: _____

LINE DRAWING:



FM-W57812

WAC LIGHTING

Dot Ceiling Mount

Fixture Type: _____
Catalog Number: _____
Project: _____
Location: _____

Model & Size	Color Temp	Finish	LED Watts	LED Lumens	Delivered Lumens
FM-W57815 15"	2700K	BK Black SS Stainless Steel	31W	2400	1773
	3000K				
	3500K				

Example: **FM-W57815F-35-BK**

•For 277V special order, add an "F" before the finish: FM-W57815F-35-SS

For custom requests please contact customs@wacighting.com

DESCRIPTION

Optimal diffuser amplifies the rightness on this durable waterproof outdoor flush mount.

FEATURES

- Lightweight, injection-molded, UV-rated acrylic diffuser enhances brightness, safety lock prevents slippage
- 277V option available for 9", 12" & 15" sizes (special order)
- Built in color temperature adjustability. Switch from 2700K/3000K/3500K
- Compact 3CCT switch installs within the junction box
- Option to pre-select color temperature or adjust in the field
- 0-10V dimming option (LDS065M010AFE-LO1) available (special order), unit dimensions: 3.4" x 1.2" x 0.5"
- ACLED driverless technology
- 5 year warranty



SPECIFICATIONS

Color Temp:	2700K,3000K,3500K
Input:	120 VAC,50/60Hz
CRI	90
Dimming:	ELV: 100-10% , TRIAC: 100-10%
Rated Life:	50,000 Hours
Mounting:	Can be mounted on ceiling or wall in all orientations
Standards:	ETL, cETL, IP65, Title 24 JA8 Compliant, Energy Star 2.0, ADA, Wet Location Listed
Construction	Weather-resistant 316 stainless steel body with thick acrylic shade

FINISHES:



WAC LIGHTING

Dot

Ceiling Mount

Fixture Type: _____
Catalog Number: _____
Project: _____
Location: _____

LINE DRAWING:

