

WAC LIGHTING

Double Diamond

Wall Sconce 4CCT

Fixture Type: _____
Catalog Number: _____
Project: _____
Location: _____

Model & Size	Color Temp	Finish	LED Watts	LED Lumens	Delivered Lumens
WS101606 6"	2700K/3000K/3500K/4000K	AB Aged Brass BK Black	15W	892	687

Example: **WS101606-BK**


For custom requests please contact customs@wacighting.com

DESCRIPTION

Sculptural and striking, Double Diamond transforms walls into art. Its bold, faceted silhouette casts a dynamic play of light and shadow, perfect for creating visual interest in any room. Designed to dazzle.

FEATURES

- Built in color temperature adjustability. Switch from 2700K/3000K/3500K/4000K
- Driver concealed within the canopy
- Can be mounted on wall in all orientations
- Illumination from all four sides
- Driver included
- 5 year warranty




SPECIFICATIONS

Color Temp:	2700K/3000K/3500K/4000K
Input:	120-277V,50/60Hz
CRI	90
Dimming:	ELV: 100-10% , TRIAC: 100-10%
Rated Life:	50,000 Hours
Mounting:	Can be mounted on wall in all orientations
Standards:	ETL, cETL, Title 24 JA8 Compliant, ADA, Damp Location Listed
Construction	Aluminum body with acrylic diffuser

FINISHES:



LINE DRAWING



WS101606

WAC LIGHTING

Double Diamond

Wall Sconce 4CCT

Fixture Type: _____
Catalog Number: _____
Project: _____
Location: _____

Model & Size	Color Temp	Finish	LED Watts	LED Lumens	Delivered Lumens
WS101620 20"	2700K/3000K/3500K/4000K	AB Aged Brass BK Black	28W	1675	1173

Example: **WS101620-BK**

For custom requests please contact customs@wacighting.com

DESCRIPTION

Sculptural and striking, Double Diamond transforms walls into art. Its bold, faceted silhouette casts a dynamic play of light and shadow, perfect for creating visual interest in any room. Designed to dazzle.

FEATURES


- Built in color temperature adjustability. Switch from 2700K/3000K/3500K/4000K
- Driver concealed within the canopy
- Can be mounted on wall in all orientations
- Illumination from all four sides
- Driver included
- 5 year warranty

SPECIFICATIONS

Color Temp:	2700K/3000K/3500K/4000K
Input:	120-277V,50/60Hz
CRI	90
Dimming:	ELV: 100-10% , TRIAC: 100-10%
Rated Life:	50,000 Hours
Mounting:	Can be mounted on wall in all orientations
Standards:	ETL, cETL, Title 24 JA8 Compliant, ADA, Damp Location Listed
Construction	Aluminum body with acrylic diffuser



FINISHES:



LINE DRAWING

