

WAC LIGHTING

Edgeless

Ceiling and Wall Mount

Fixture Type: _____
Catalog Number: _____
Project: _____
Location: _____

Model & Size	Color Temp & CRI	Watt	Lumens	Finish
FM-240505	9CS	15W	1330	BK Black
FM-240508	2700K/3000K/3500K/4000K/5000K - 90	20W	1985	WT White
FM-240512	9CS 2700K/3000K/3500K/4000K/5000K - 90	30W	2750	

Example: **FM-240505-9CS-BK**

DESCRIPTION

Edgeless LED luminaires are designed with a low profile and slim trim. They are engineered for smooth, glare-free, consistent illumination. A welcome addition to ceilings and walls for various applications.

FEATURES

- Multiple LED array for uniform illumination
- Designed with slim trim to maximize light emitting surface
- 5-CCT Switchable between 2700K and 5000K
- Driver concealed within the fixture
- 5 year warranty

SPECIFICATIONS

Construction	Aluminum with white acrylic diffuser
Power:	15W, 20W, 30W
Input:	120 VAC, 50/60Hz
Dimming:	ELV: 100-5% , TRIAC: 100-5%
Light Source:	Integrated LED
Lens:	Acrylic Diffuser
Rated Life:	50,000 Hours
Mounting:	Installs over a 3", 4" or 3/0-4/0 hybrid junction box, Can be mounted on ceiling or wall in all orientations
Finish:	Electrostatically Powder Coated: Black, White
Operating Temp:	-4°F to 104°F (-20°C to 40°C)
Standards:	ETL, cETL, Wet Location Listed, ADA, Title 24 JA8 Compliant



FINISHES:

