

Ion 2" Round

Remodel Downlight

Catalog Number:			
Project:			
Location:			

Model	Beam	Color Temp & CRI	Lumens	CBCP	Finish
R2DRDR	F 35°	930 3000K - 90	710	993	WT White

Example: R2DRDR-F930-WT

DESCRIPTION

Minimum profile downlight with metal conduit and driver included for easy remodel or new construction installation.

FFATURES

- Sold as remodel, but new construction frame available
- Metal Conduit with Quick Connect to allow for easy installation
- Driver included
- 5 year warranty

SPECIFICATIONS

Construction Die-cast Aluminum with 20-gauge Cold Rolled Steel Driver Box

Power: 9W

Input: 120-277 VAC,50/60Hz

Dimming: ELV: 100-10%, TRIAC: 100-5%

Light Source: Integrated LED
Lens: Frosted TIR lens
Rated Life: 50,000 Hours

Mounting: Heavy gauge rentention clips secures fixture to ceiling

Cut Out: 3"

Finish: Electrostatically Powder Coated: White

Ceiling Thickness: 1/2" - 1 1/2"

Operating Temp: -4°F to 104°F (-20°C to 40°C)

Standards: ETL, cETL, Wet Location Listed, Energy Star 2.0, Title 24 JA8

Compliant, Airtight, IC




FINISHES:


Fixture Type:



White

LINE DRAWING







Ion 2" Round

Remodel Downlight

Fixture Type:	_
Catalog Number:	
Project:	_
Location:	-

ACCESSORIES					
	Model	Description	Finish		
	R2DRDN-FRAME	lon 2"			