WAC LIGHTING

LANDSCAPE 3" IN-GROUND SHROUD

Fixture Type:

Catalog Number:

Project:

Location:

Model & Voltage	Color Temp & CRI	Lumens	Finish
❍ 5030-SHR	3 0		❍ BBR Bronze on Brass ❍ BZ Bronze on Aluminum

Example: **5030-SHR-BBR**

DESCRIPTION

Anti-glare shroud for Inground Light

FEATURES

• Glare control accessory for inground light

SPECIFICATIONS

Construction	Die-cast brass, Die-cast aluminum
Finish:	Enamel Coated Bronze on Aluminum, Enamel Coated Bronze on Brass

FINISHES:

Bronze on Aluminum

Bronze on Brass

WAC Lighting retains the right to modify the design of our products at any time as part of the company's continuous improvement program. September 2026

WAC LIGHTING

3" Inground 12V

Landscape Recessed LED

Fixture Type:

Catalog Number:

Project:

Location:

Model & Voltage	Color Temp & CRI	Lumens	Finish
❍ 5031 9-15 VAC	❍ 3000K 85 ❍ 2700K 85	505 505	❍ BBR Bronze on Brass ❍ BZ Bronze on Aluminum

Example: **5031-27BBR**

DESCRIPTION

Simplicity meets function and durability with this ground breaking patented WAC Landscape Lighting Accent Light. One fixture fits all applications, eliminating the need to choose from dozens of varying beam angles and light outputs found in traditional landscape fixtures. A quick and simple twist of the fixture at indexed intervals allows continuous adjustment of the beam angle to perform the consolidated task of dozens of comparable landscape lights. Factory sealed water tight and IP66 Rated for protection against high-pressure water jets and outdoor elements. Available in a bronze finish with an aluminum construction or with a solid brass construction. Brass may provide enhanced protection against corrosive elements found in coastal/marine environments.

FEATURES

- Tiltable and adjustable beam angle
- Integral dimmer
- IP67 Rated, protected from temporary immersion under water
- Drive over up to 4500lbs
- Available Concrete Pour Kit
- 6ft lead wire and direct burial gel-filled wire nuts included
- Maintains constant lumen output against voltage drop
- MLV dimmable with remote MLV dimmer
- Transformer required
- 10 yrs warranty

FINISHES:

Bronze on Aluminum

Bronze on Brass

SPECIFICATIONS

Construction	Solid die-cast brass, Corrosion resistant aluminum alloy
Power:	2-12W
Input:	9-15 VAC,50/60Hz
Dimming:	Integral Brightness Control
Light Source:	High Output COB LED, 3 Step Mac Adam Ellipse
Lens:	Tempered Clear Lens
Rated Life:	55,000 Hours
Finish:	Enamel Coated Bronze on Aluminum, Enamel Coated Bronze on Brass
Operating Temp:	-40°F to 122°F (-40°C to 50°C)
Standards:	UL, cUL, Wet Location Listed, IP67

LINE DRAWING



REPLACEMENT PARTS

M5031LE-27BZ - LED Engine
M5031LE-30BZ - LED Engine

WAC Lighting retains the right to modify the design of our products at any time as part of the company's continuous improvement program. September 2026