

WAC LIGHTING

Lotos 4" & 6" Round

Adjustable Downlight 5CCT

Fixture Type: _____
 Catalog Number: _____
 Project: _____
 Location: _____

Model	Beam	Color Temp & CRI	Lumens	CBCP	Finish
R4ERAR R6ERAR	W 45°	9CS 2700K/3000K/3500K/4000K/5000K - 90	1290 1340 690 800	1920 1896 925 1020	BK Black WT White

Example: **R4ERAR-W9CS-BK**

FEATURES


- 5-CCT Switchable between 2700K and 5000K
- Multiple LED array for uniform illumination
- Rotatable multi-axis gimbal ring
- Driver included
- 5 year warranty

SPECIFICATIONS


Construction	Steel with frosted TIR lens
Power:	9W, 15W
Input:	120 -277 VAC,50/60Hz
Dimming:	ELV: 100-5% , TRIAC: 100-5%
Light Source:	Integrated LED
Lens:	Translucent acrylic diffuser
Rated Life:	50,000 Hours
Mounting:	Heavy gauge retention clips secures fixture to ceiling
Cut Out:	4 1/4", 5"
Finish:	Electrostatically powder coated Black, Electrostatically powder coated White
Ceiling Thickness:	1/2" - 1"
Operating Temp:	-4°F to 104°F (-20°C to 40°C)
Standards:	ETL, cETL, Wet Location Listed, Title 24 JA8 Compliant, Airtight, IC



FINISHES:



LINE DRAWING



R4ERAR


WAC LIGHTING

Lotos 4" & 6" Round

Adjustable Downlight 5CCT

Fixture Type: _____
Catalog Number: _____
Project: _____
Location: _____

ACCESSORIES

	<i>Model</i>	<i>Description</i>	<i>Finish</i>
	RER-FRAME	Lotos	