

WAC LIGHTING

Ocularc 1.0

8W Open Reflector Square

Fixture Type: _____
Catalog Number: _____
Project: _____
Location: _____

Model	Beam	Color Temp & CRI	Lumens	CBCP	Finish
R1BSD-08	F 45°	927 2700K - 90	530	830	BK Black
		930 3000K - 90	575	897	BN Brushed Nickel
	N 25°	927 2700K - 90	615	2211	HZWT Haze/White
		930 3000K - 90	665	2390	WT White

Example: **R1BSD-08-F927-BK**

DESCRIPTION


Engineered with state of the art LED and driver technology, Ocularc 3.0, 2.0, 1.0 family of recessed lighting offers various styles, IC and Airtight Rated New Construction and Remodel, and low glare optical distributions to beautifully illuminate a diverse range of applications.

FEATURES

- Cutout 2 1/2"
- Single spot light source
- Ceiling thickness: 1/2" - 1"
- Sold as New Construction, may be reconfigured in the field for Remodel
- Driver concealed within the fixture
- 5 year warranty

SPECIFICATIONS

Construction	Die-cast aluminum trim with aluminum heat sink
Power:	7.5W
Input:	120 VAC, 50/60Hz
Dimming:	ELV: 100-5% , YES
Light Source:	Integrated LED, 3 Step Mac Adam Ellipse
Rated Life:	50,000 Hours
Cut Out:	2 1/2"
Finish:	Electrostatically Powder Coated: White, Haze/White, Black, Electroplated Brushed Nickel
Ceiling Thickness:	1/2" - 1"
Operating Temp:	-4°F to 104°F (-20°C to 40°C)
Standards:	ETL, cETL, Wet Location Listed, Energy Star 2.0, Title 24 JA8 Compliant, Airtight, IC



FINISHES:

