

# WAC LIGHTING

## Ocularc 1.0

### 8W Open Reflector Round

Fixture Type: \_\_\_\_\_  
Catalog Number: \_\_\_\_\_  
Project: \_\_\_\_\_  
Location: \_\_\_\_\_

Model	Beam	Color Temp & CRI	Lumens	CBCP	Finish
R1BRD-08	F 45°	927 2700K - 90	530	825	BK Black
		930 3000K - 90	570	892	BN Brushed Nickel
	N 25°	927 2700K - 90	620	2217	HZWT Haze/White
		930 3000K - 90	670	2397	WT White

Example: **R1BRD-08-F927-BK**

#### DESCRIPTION

Engineered with state of the art LED and driver technology, Ocularc 3.0, 2.0, 1.0 family of recessed lighting offers various styles, IC and Airtight Rated New Construction and Remodel, and low glare optical distributions to beautifully illuminate a diverse range of applications.

#### FEATURES

- Cutout 2 1/2"
- Single spot light source
- Ceiling thickness: 1/2" - 1"
- Sold as New Construction, may be reconfigured in the field for Remodel
- Driver concealed within the fixture
- 5 year warranty

#### SPECIFICATIONS

<b>Construction</b>	Die-cast aluminum trim with aluminum heat sink
<b>Power:</b>	7.5W
<b>Input:</b>	120 VAC, 50/60Hz
<b>Dimming:</b>	ELV: 100-5% , YES
<b>Light Source:</b>	Integrated LED, 3 Step Mac Adam Ellipse
<b>Rated Life:</b>	50,000 Hours
<b>Cut Out:</b>	2 1/2"
<b>Finish:</b>	Electrostatically Powder Coated: White, Haze/White, Black, Electroplated Brushed Nickel
<b>Ceiling Thickness:</b>	1/2" - 1"
<b>Operating Temp:</b>	-4°F to 104°F (-20°C to 40°C)
<b>Standards:</b>	ETL, cETL, Wet Location Listed, Energy Star 2.0, Title 24 JA8 Compliant, Airtight, IC



#### FINISHES:

