

WAC LIGHTING

Ocularc 2.0

11W Open Reflector Square

Fixture Type: _____
 Catalog Number: _____
 Project: _____
 Location: _____

Model	Beam	Color Temp & CRI	Lumens	CBCP	Finish
R2BSD-11	F 45°	927 2700K - 90	905	1451	BK Black
		930 3000K - 90	955	1527	BN Brushed Nickel
	N 25°	927 2700K - 90	890	2612	HZWT Haze/White
		930 3000K - 90	935	2749	WT White

Example: **R2BSD-11-F927-BK**

DESCRIPTION

Engineered with state of the art LED and driver technology, Ocularc 3.0, 2.0, 1.0 family of recessed lighting offers various styles, IC and Airtight Rated New Construction and Remodel, and low glare optical distributions to beautifully illuminate a diverse range of applications.

FEATURES

- Cutout 3 1/16"
- Single spot light source
- Ceiling thickness: 1/2" - 1"
- Sold as New Construction, may be reconfigured in the field for Remodel
- Driver concealed within the fixture
- 5 year warranty

SPECIFICATIONS

Construction	Die-cast aluminum trim with aluminum heat sink
Power:	11W
Input:	120 VAC, 50/60Hz
Dimming:	ELV: 100-5% , 0-10V: 100-5% , TRIAC: 100-5%
Light Source:	Integrated LED, 3 Step Mac Adam Ellipse
Rated Life:	50,000 Hours
Cut Out:	3 1/16"
Finish:	Electrostatically Powder Coated: White, Haze/White, Black, Brushed Nickel
Ceiling Thickness:	1/2" - 1"
Operating Temp:	-4°F to 104°F (-20°C to 40°C)
Standards:	ETL, cETL, Wet Location Listed, Energy Star 2.0, Title 24 JA8 Compliant, Airtight, IC



FINISHES:



LINE DRAWING

INTEGRAL HOUSING AND TRIM: BOTH NEW CONSTRUCTION & REMODEL

NEW CONSTRUCTION CONFIGURATION
 IC-Rated, Airtight

