

WAC LIGHTING

Oyster

Pendant 4CCT

Fixture Type: _____
 Catalog Number: _____
 Project: _____
 Location: _____

Model & Size	Color Temp	Finish	LED Watts	LED Lumens	Delivered Lumens
PD-41433 33"	2700K	AB Aged Brass BC Black Chrome	38 W	2642	1482
	3000K				
	3500K				
	4000K				

Example: **PD-41433-40-BC**

For custom requests please contact customs@wacighting.com

DESCRIPTION

Organic in nature, a white diffuser undulates within a band of black. Uniquely flowing, this pendant supplies contemporary interiors with warm LED light.

FEATURES


- Low profile, adjustable powered aircraft cables for an ultra-clean look
- May be mounted on slope ceiling
- Built in color temperature adjustability. Switch from 2700K/3000K/3500K/4000K
- Spin-on round canopy with minimal hardware
- Option to pre-select color temperature or adjust in the field
- Driver concealed within the canopy
- 5 Year warranty

SPECIFICATIONS


Color Temp:	2700K,3000K,3500K,4000K
Input:	120-277V,50/60Hz
CRI	90
Dimming:	ELV: 100-10% , 0-10V: 100-10% , TRIAC: 100-5%
Rated Life:	50,000 Hours
Standards:	ETL, cETL, Title 24 JA8 Compliant, Damp Location Listed
Construction	Aluminum body, silicone diffuser



FINISHES:



LINE DRAWING:



PD-41433

WAC LIGHTING

Oyster

Pendant 4CCT

Fixture Type: _____
 Catalog Number: _____
 Project: _____
 Location: _____

Model & Size	Color Temp	Finish	LED Watts	LED Lumens	Delivered Lumens
PD-41442 42"	2700K	AB Aged Brass BC Black Chrome	57W	3500	2744
	3000K				
	3500K				
	4000K				

Example: **PD-41442-40-BC**

For custom requests please contact customs@wacighting.com

DESCRIPTION

Organic in nature, a white diffuser undulates within a band of black. Uniquely flowing, this pendant supplies contemporary interiors with warm LED light.

FEATURES


- Low profile, adjustable powered aircraft cables for an ultra-clean look
- May be mounted on slope ceiling
- Built in color temperature adjustability. Switch from 2700K/3000K/3500K/4000K
- Spin-on round canopy with minimal hardware
- Option to pre-select color temperature or adjust in the field
- Driver concealed within the canopy
- 5 Year warranty

SPECIFICATIONS


Color Temp:	2700K,3000K,3500K,4000K
Input:	120-277V,50/60Hz
CRI	90
Dimming:	ELV: 100-10% , 0-10V: 100-10% , TRIAC: 100-5%
Rated Life:	50,000 Hours
Standards:	ETL, cETL, Title 24 JA8 Compliant, Damp Location Listed
Construction	Aluminum body, silicone diffuser



FINISHES:



LINE DRAWING:



PD-41442