WAC LIGHTING

Planets

Flush Mount 3500K

Model & Size	Color Temp	Finish	LED Watts	LED Lumens	Delivered Lumens
FM-16617 17"	3500K	BN Brushed Nickel	60W	5310	2355

Example: **FM-16617-BN**

For custom requests please contact customs@waclighting.com

DESCRIPTION

Cosmically proportioned decorative ceiling-mount luminaires. Illuminate evenly for an out of this world experience.

FEATURES

• Large diameter makes a great addition to large rooms or high-ceiling applications
• Low-profile fixture with maximum illumination
• Extruded aluminum trim with no visible hardware
• Silk-screened glass diffuser with a white ceramic glaze
• Driver concealed within the fixture
• 5 year warranty

SPECIFICATIONS

|	
Color Temp:	3500K
Input:	120-277V,50/60Hz
CRI	90
Dimming:	ELV: 100-10%
Rated Life:	63,000 Hours
Mounting:	Can be mounted on ceiling or wall in all orientations
Standards:	ETL, cETL, ADA, Damp Location Listed
Construction	Aluminum hardware with silkscreen glass diffuser

FINISHES:

Brushed
Nickel

LINE DRAWING:

17" 2"

waclighting.com | Phone (800) 526.2588 | **Fax** (800) 526.2585 | **Headquarters/Eastern Distribution Center** 44 Harbor Park Drive Port Washington, NY 11050

WAC Lighting retains the right to modify the design of our products at any time as part of the company's continuous improvement program. March 2025

1

WAC LIGHTING

Planets

Flush Mount 3500K

Model & Size	Color Temp	Finish	LED Watts	LED Lumens	Delivered Lumens
FM-16622 22"	3500K	BN Brushed Nickel	88W	8200	3460

Example: **FM-16622-BN**

For custom requests please contact customs@waclighting.com

DESCRIPTION

Cosmically proportioned decorative ceiling-mount luminaires. Illuminate evenly for an out of this world experience.

FEATURES

• Large diameter makes a great addition to large rooms or high-ceiling applications
• Low-profile fixture with maximum illumination
• Extruded aluminum trim with no visible hardware
• Silk-screened glass diffuser with a white ceramic glaze
• Driver concealed within the fixture
• 5 year warranty

SPECIFICATIONS

Color Temp:	3500K
Input:	120-277V,50/60Hz
CRI	90
Dimming:	ELV: 100-10%
Rated Life:	63,000 Hours
Mounting:	Can be mounted on ceiling or wall in all orientations
Standards:	ETL, cETL, ADA, Damp Location Listed
Construction	Aluminum hardware with silkscreen glass diffuser

FINISHES:

Brushed Nickel

LINE DRAWING:

22"   2"

waclighting.com | Phone (800) 526.2588 | **Fax** (800) 526.2585 | **Headquarters/Eastern Distribution Center** 44 Harbor Park Drive Port Washington, NY 11050

WAC Lighting retains the right to modify the design of our products at any time as part of the company's continuous improvement program. March 2025

2