Fixture Type:

Catalog Number:

Project:

Location:

WAC LIGHTING

Pop-In 4" Round 5CCT

New Construction Downlight

Model	Beam	Color Temp & CRI	Lumens	CBCP	Finish
❍ R4DRDN	❍ F 45°	❍ 9CS 2700K/3000K/3500K/4000K/5000K - 90	1080 870	1309 1189	❍ BK Black ❍ WT White

Example: **R4DRDN-F9CS-BK**

FEATURES

- 5-CCT Switchable between 2700K and 5000K
- Electrical box located on back of fixture to allow easy installation
- Sold as new construction, may be configured in field for remodel
- Driver concealed within the fixture
- 5 year warranty

SPECIFICATIONS

Construction	Die-cast Aluminum with 20-gauge Cold Rolled Steel Junction Box
Power:	12W
Input:	120-277 VAC,50/60Hz
Dimming:	ELV: 100-5% , TRIAC: 100-5%
Light Source:	Integrated LED
Lens:	Frosted TIR lens
Rated Life:	50,000 Hours
Mounting:	New construction housings included with hanger bars
Cut Out:	4 1/8"
Finish:	Electrostatically Powder Coated: Black, White
Ceiling Thickness:	1/2" - 1 1/2"
Operating Temp:	-4°F to 104°F (-20°C to 40°C)
Standards:	ETL, cETL, Wet Location Listed, Title 24 JA8 Compliant, Airtight, IC

FINISHES:



Black White

LINE DRAWING



R4DRDN

WAC Lighting retains the right to modify the design of our products at any time as part of the company's continuous improvement program. November 2026