WAC LIGHTING

Fixture Type:

Catalog Number:

Project:

Location:

# Quick Connect™

## 3 Points Rectangular Mirrored Canopy

Model & Product

❍ QMP-G3RE-MR 3-Point rectangular mirrored canopy

Example: **QMP-G3RE-MR**

### FEATURES

- For use with any of our Quick Connect™ pendants
- 60W integral electronic transformer for each drop
- Smooth and continuous ELV dimming
- Includes accent caps in Brushed Nickel and Chrome to match any of our socket sets
- 5 year warranty

### SPECIFICATIONS

| | |
|---|---|
| **Construction** | Mirrored Canopy with plated hardware |
| **Power:** | Max 3 X 60W |
| **Input:** | 120 VAC,50/60Hz |
| **Standards:** | UL, cUL, Dry Location Listed |



*WAC Lighting retains the right to modify the design of our products at any time as part of the company's continuous improvement program. October 2026*

Fixture Type:

Catalog Number:

Project:

Location:

# WAC LIGHTING

## Genesis

### Quick Connect™ Pendant 3000K

| Model & Wattage | Lumens | Color Temp & CRI | Finish |
|---|---|---|---|
| ❍ QP-LED311 5W | 210 | 3000K 85 | ❍ BN/BN Brushed Nickel |

Example: **QP-LED311-BN/BN**

**DESCRIPTION**

With dual uplight and downlight LED engines, Genesis integrates high performance with ambient lighting. An evolutionary design in a diminutive size resulting in a stunning decorative accent.

**FEATURES**

- All socket sets include 12ft wire that may be cut in the field
- Free of projected heat, ultraviolet and infrared radiation
- 5 year warranty

**SPECIFICATIONS**

| | |
|---|---|
| **Construction** | Solid Clear Seeded Glass with electroplated metal hardware |
| **Power:** | 5W |
| **Input:** | 12 VAC,50/60Hz |
| **Dimming:** | ELV: 100-15% |
| **Light Source:** | Integrated LED |
| **Rated Life:** | 50,000 Hours |
| **Finish:** | Electroplated Brushed Nickel |
| **Operating Temp:** | -4°F to 104°F (-20°C to 40°C) |
| **Standards:** | UL, cUL, Dry Location Listed |

**FINISHES:**

Brushed Nickel

Fixture Type:

Catalog Number:

Project:

Location:

# WAC LIGHTING

## Uber

### Quick Connect™ Pendant 3000K

| Model & Wattage | Lumens | Color Temp & CRI | Finish |
|---|---|---|---|
| ❍ QP-LED315 5W | 180 | 3000K 85 | ❍ PT/BN Platinum/Brushed Nickel<br>❍ PT/CH Platinum/Chrome |

Example: **QP-LED315-PT/BN**

**DESCRIPTION**

Discover soft sparkling secrets by peering through the blades of Uber, a brilliantly accented LED pendant with a glimmering translucent diffuser that gently reveals light through distinctive Die-cast metal lines.

**FEATURES**

- All socket sets include 6ft wire that may be cut in the field
- Free of projected heat, ultraviolet and infrared radiation
- 5 year warranty

**SPECIFICATIONS**

| | |
|---|---|
| **Construction** | Metal pendant with electroplated metal hardware |
| **Power:** | 5W |
| **Input:** | 12 VAC,50/60Hz |
| **Dimming:** | ELV: 100-15% |
| **Light Source:** | Integrated LED |
| **Rated Life:** | 50,000 Hours |
| **Finish:** | Electrostatically Powder Coated: Platinum/Chrome, Platinum/Brushed Nickel |
| **Operating Temp:** | -4°F to 104°F (-20°C to 40°C) |
| **Standards:** | UL, cUL, Dry Location Listed |

**FINISHES:**

Platinum/Brushed Nickel

Platinum/Chrome



*WAC Lighting retains the right to modify the design of our products at any time as part of the company's continuous improvement program. October 2026*

Fixture Type:

Catalog Number:

Project:

Location:

# WAC LIGHTING

## Ingo

### Quick Connect™ Pendant 3000K

| Model & Wattage | Lumens | Color Temp & CRI | Finish |
|---|---|---|---|
| ❍ QP-913LED | 110 | | ❍ CF/BN Clear Frosted/Brushed Nickel |
| ❍ QP913 | 330 | | ❍ CF/CH Clear Frosted/Chrome |

Example: **QP-913LED-CF/BN**

**DESCRIPTION**

Mouth blown handcrafted pendants inspired by dripping ice crystals and other elements of winter, Ingo features the clean design of mouth blown German art glass for an elegant statement.

**FEATURES**

- All socket sets include 6ft wire that may be cut in the field
- Lamp included
- Free of projected heat, ultraviolet and infrared radiation
- 5 year warranty

**SPECIFICATIONS**

| | |
|---|---|
| **Construction** | Mouth blown glass shade with electroplated metal hardware, Mouth blown glass shade with plated metal hardware |
| **Input:** | 12 VAC,50/60Hz |
| **Dimming:** | ELV: 100-15% |
| **Light Source:** | Xenon Bi-Pin Max 50W, LED Bi-Pin 2.7W, 110lm, 3000K, 85CRI |
| **Rated Life:** | 50,000 Hours |
| **Finish:** | Clear Frosted/Chrome, Clear Frosted/Brushed Nickel |
| **Operating Temp:** | -4°F to 104°F (-20°C to 40°C) |
| **Standards:** | UL, cUL, Dry Location Listed |

**FINISHES:**

Clear Frosted /Brushed Nickel

Clear Frosted /Chrome

Fixture Type:

Catalog Number:

Project:

Location:

# WAC LIGHTING

## Tulum

### Quick Connect™ Pendant 3000K

| Model & Wattage | Lumens | Color Temp & CRI | Finish |
|---|---|---|---|
| ❍ QP-914LED<br>❍ QP914 | 235 | | ❍ FR/BN Frosted/Brushed Nickel<br>❍ FR/CH Frosted/Chrome |

Example: **QP-914LED-FR/BN**

**DESCRIPTION**

A frosted glass pendant carefully etched and paneled to reveal the mini pendant's inner light, Tulum offers a visually soft option for a contemporary space using a modern design that is perfect above a counter, bar or table.

**FEATURES**

- All socket sets include 6ft wire that may be cut in the field
- Lamp included
- Free of projected heat, ultraviolet and infrared radiation
- 5 year warranty

**SPECIFICATIONS**

| | |
|---|---|
| **Construction** | Mouth blown glass shade with plated metal hardware, Mouth blown glass shade with electroplated metal hardware |
| **Input:** | 12 VAC,50/60Hz |
| **Dimming:** | ELV: 100-15% |
| **Light Source:** | LED Bi-Pin 2.7W, 110lm, 3000K, 85CRI, Xenon Bi-Pin Max 50W |
| **Rated Life:** | 50,000 Hours |
| **Finish:** | Frosted/Chrome, Frosted/Brushed Nickel |
| **Operating Temp:** | -4°F to 104°F (-20°C to 40°C) |
| **Standards:** | UL, cUL, Dry Location Listed |

**FINISHES:**

Frosted/Brushed Nickel

Frosted/Chrome



*WAC Lighting retains the right to modify the design of our products at any time as part of the company's continuous improvement program. October 2026*

Fixture Type:

Catalog Number:

Project:

Location:

# WAC LIGHTING

## Tikal

### Quick Connect™ Pendant 3000K

| Model & Wattage | Lumens | Color Temp & CRI | Finish |
|---|---|---|---|
| ❍ QP-915LED<br>❍ QP915 | 235 | | ❍ CF/BN Clear Frosted/Brushed Nickel<br>❍ CF/CH Clear Frosted/Chrome |

Example: **QP-915LED-CF/BN**

**DESCRIPTION**

Mouth blown handcrafted pendants inspired by dripping ice crystals and other elements of winter, Ingo features the clean design of mouth blown German art glass for an elegant statement.

**FEATURES**

- All socket sets include 6ft wire that may be cut in the field
- Lamp included
- Free of projected heat, ultraviolet and infrared radiation
- 5 year warranty

**SPECIFICATIONS**

| | |
|---|---|
| **Construction** | Mouth blown glass shade with plated metal hardware, Mouth blown glass shade with electroplated metal hardware |
| **Input:** | 12 VAC,50/60Hz |
| **Dimming:** | ELV: 100-15% |
| **Light Source:** | LED Bi-Pin 2.7W, 110lm, 3000K, 85CRI, Xenon Bi-Pin Max 50W |
| **Rated Life:** | 50,000 Hours |
| **Finish:** | Clear Frosted/Chrome, Clear Frosted/Brushed Nickel |
| **Operating Temp:** | -4°F to 104°F (-20°C to 40°C) |
| **Standards:** | UL, cUL, Dry Location Listed |

**FINISHES:**

Clear Frosted /Brushed Nickel

Clear Frosted /Chrome



*WAC Lighting retains the right to modify the design of our products at any time as part of the company's continuous improvement program. October 2026*

Fixture Type:

Catalog Number:

Project:

Location:

# WAC LIGHTING

## Clarity

### Quick Connect™ Pendant 3000K

| Model & Wattage | Lumens | Color Temp & CRI | Finish |
|---|---|---|---|
| ❍ QP-LED916<br>❍ QP916 | 330 | | ❍ CL/BN<br>Clear/Brushed Nickel<br>❍ CL/CH<br>Clear/Chrome |

Example: **QP-LED916-CL/BN**

**DESCRIPTION**

Lovingly created by hand by Germany's finest glass blowers, the Clarity art glass pendant demonstrates dazzling spectral properties and can be mounted for use on track, rail or canopies.

**FEATURES**

- All socket sets include 6ft wire that may be cut in the field
- Lamp included
- Free of projected heat, ultraviolet and infrared radiation
- 5 year warranty

**SPECIFICATIONS**

| | |
|---|---|
| **Construction** | Mouth blown glass shade with electroplated metal hardware, Mouth blown glass shade with plated metal hardware |
| **Input:** | 12 VAC,50/60Hz |
| **Dimming:** | ELV: 100-15% |
| **Light Source:** | Xenon Bi-Pin Max 50W, Integrated LED 4W, 330lm, 3000K, 85CRI |
| **Rated Life:** | 50,000 Hours |
| **Finish:** | Clear/Brushed Nickel, Clear/Chrome |
| **Operating Temp:** | -4°F to 104°F (-20°C to 40°C) |
| **Standards:** | UL, cUL, Dry Location Listed |

**FINISHES:**

Clear/Brushed Nickel

Clear/Chrome



*WAC Lighting retains the right to modify the design of our products at any time as part of the company's continuous improvement program. October 2026*

Fixture Type:

Catalog Number:

Project:

Location:

# WAC LIGHTING

## Bullet

### Quick Connect™ Pendant 3000K

| Model & Wattage | Lumens | Color Temp & CRI | Finish |
|---|---|---|---|
| ❍ QP-LED966<br>❍ QP966 | 330 | | ❍ BN/BN Brushed Nickel<br>❍ CH/CH Chrome |

Example: **QP-LED966-BN/BN**

**DESCRIPTION**

Modern minimalist form derived from function, Bullet pendants are available in two hardware matching metal finishes. The white interior of the shade reflects light onto the surface below.

**FEATURES**

- All socket sets include 6ft wire that may be cut in the field
- Lamp included
- Free of projected heat, ultraviolet and infrared radiation
- 5 year warranty

**SPECIFICATIONS**

| | |
|---|---|
| **Construction** | Aluminum Shade with electroplated metal hardware, Aluminum Shade with plated metal hardware |
| **Input:** | 12 VAC,50/60Hz |
| **Dimming:** | ELV: 100-15% |
| **Light Source:** | Xenon Bi-Pin Max 50W, Integrated LED 6.4W, 450lm, 3000K, 85 CRI |
| **Rated Life:** | 50,000 Hours |
| **Finish:** | Brushed Nickel, Chrome |
| **Operating Temp:** | -4°F to 104°F (-20°C to 40°C) |
| **Standards:** | UL, cUL, Dry Location Listed |

**FINISHES:**

Brushed Nickel

Chrome