

WAC LIGHTING

Quick Connect™

12 Points Round Mirrored Canopy

Model & Product

QMP-G12RN-MR 12-Point round mirrored canopy

Fixture Type: _____

Catalog Number: _____

Project: _____

Location: _____


Example: **QMP-G12RN-MR**

FEATURES

- For use with any of our Quick Connect™ pendants
- 60W integral electronic transformer for each drop
- Smooth and continuous ELV dimming
- Includes accent caps in Brushed Nickel and Chrome to match any of our socket sets
- 5 year warranty

SPECIFICATIONS

Construction	Mirrored Canopy with plated hardware
Power:	Max 12 X 60W
Input:	120 VAC, 50/60Hz
Standards:	UL, cUL, Dry Location Listed



WAC LIGHTING

Genesis

Quick Connect™ Pendant 3000K

Model & Wattage	Lumens	Color Temp & CRI	Finish
QP-LED311 5W	210	3000K 85	BN/BN Brushed Nickel

Fixture Type: _____
Catalog Number: _____
Project: _____
Location: _____

Example: **QP-LED311-BN/BN**

DESCRIPTION

With dual uplight and downlight LED engines, Genesis integrates high performance with ambient lighting. An evolutionary design in a diminutive size resulting in a stunning decorative accent.

FEATURES

- All socket sets include 12ft wire that may be cut in the field
- Free of projected heat, ultraviolet and infrared radiation
- 5 year warranty

SPECIFICATIONS

Construction	Solid Clear Seeded Glass with electroplated metal hardware
Power:	5W
Input:	12 VAC, 50/60Hz
Dimming:	ELV: 100-15%
Light Source:	Integrated LED
Rated Life:	50,000 Hours
Finish:	Electroplated Brushed Nickel
Operating Temp:	-4°F to 104°F (-20°C to 40°C)
Standards:	UL, cUL, Dry Location Listed



FINISHES:



Brushed Nickel

WAC LIGHTING

Uber

Quick Connect™ Pendant 3000K

Model & Wattage	Lumens	Color Temp & CRI	Finish
QP-LED315 5W	180	3000K 85	PT/BN Platinum/Brushed Nickel PT/CH Platinum/Chrome

Fixture Type: _____
Catalog Number: _____
Project: _____
Location: _____

Example: **QP-LED315-PT/BN**

DESCRIPTION

Discover soft sparkling secrets by peering through the blades of Uber, a brilliantly accented LED pendant with a glimmering translucent diffuser that gently reveals light through distinctive Die-cast metal lines.

FEATURES


- All socket sets include 6ft wire that may be cut in the field
- Free of projected heat, ultraviolet and infrared radiation
- 5 year warranty

SPECIFICATIONS

Construction	Metal pendant with electroplated metal hardware
Power:	5W
Input:	12 VAC,50/60Hz
Dimming:	ELV: 100-15%
Light Source:	Integrated LED
Rated Life:	50,000 Hours
Finish:	Electrostatically Powder Coated: Platinum/Chrome, Platinum/Brushed Nickel
Operating Temp:	-4°F to 104°F (-20°C to 40°C)
Standards:	UL, cUL, Dry Location Listed



FINISHES:



WAC LIGHTING

Ingo

Quick Connect™ Pendant 3000K

Model & Wattage	Lumens	Color Temp & CRI	Finish
QP-913LED	110		CF/BN Clear Frosted/Brushed Nickel
QP913	330		CF/CH Clear Frosted/Chrome

Fixture Type: _____
Catalog Number: _____
Project: _____
Location: _____

Example: **QP-913LED-CF/BN**

DESCRIPTION

Mouth blown handcrafted pendants inspired by dripping ice crystals and other elements of winter, Ingo features the clean design of mouth blown German art glass for an elegant statement.

FEATURES

- All socket sets include 6ft wire that may be cut in the field
- Lamp included
- Free of projected heat, ultraviolet and infrared radiation
- 5 year warranty

SPECIFICATIONS

Construction	Mouth blown glass shade with electroplated metal hardware, Mouth blown glass shade with plated metal hardware
Input:	12 VAC,50/60Hz
Dimming:	ELV: 100-15%
Light Source:	Xenon Bi-Pin Max 50W, LED Bi-Pin 2.7W, 110lm, 3000K, 85CRI
Rated Life:	50,000 Hours
Finish:	Clear Frosted/Chrome, Clear Frosted/Brushed Nickel
Operating Temp:	-4°F to 104°F (-20°C to 40°C)
Standards:	UL, cUL, Dry Location Listed



FINISHES:



Clear Frosted/Brushed Nickel Clear Frosted/Chrome

WAC LIGHTING

Tulum

Quick Connect™ Pendant 3000K

Model & Wattage	Lumens	Color Temp & CRI	Finish
QP-914LED QP914	235		FR/BN Frosted/Brushed Nickel FR/CH Frosted/Chrome

Fixture Type: _____
Catalog Number: _____
Project: _____
Location: _____

Example: **QP-914LED-FR/BN**

DESCRIPTION

A frosted glass pendant carefully etched and paneled to reveal the mini pendant's inner light, Tulum offers a visually soft option for a contemporary space using a modern design that is perfect above a counter, bar or table.

FEATURES


- All socket sets include 6ft wire that may be cut in the field
- Lamp included
- Free of projected heat, ultraviolet and infrared radiation
- 5 year warranty

SPECIFICATIONS

Construction	Mouth blown glass shade with plated metal hardware, Mouth blown glass shade with electroplated metal hardware
Input:	12 VAC, 50/60Hz
Dimming:	ELV: 100-15%
Light Source:	LED Bi-Pin 2.7W, 110lm, 3000K, 85CRI, Xenon Bi-Pin Max 50W
Rated Life:	50,000 Hours
Finish:	Frosted/Chrome, Frosted/Brushed Nickel
Operating Temp:	-4°F to 104°F (-20°C to 40°C)
Standards:	UL, cUL, Dry Location Listed



FINISHES:



WAC LIGHTING

Tikal

Quick Connect™ Pendant 3000K

Model & Wattage	Lumens	Color Temp & CRI	Finish
QP-915LED QP915	235		CF/BN Clear Frosted/Brushed Nickel CF/CH Clear Frosted/Chrome

Fixture Type: _____
Catalog Number: _____
Project: _____
Location: _____

Example: **QP-915LED-CF/BN**

DESCRIPTION

Mouth blown handcrafted pendants inspired by dripping ice crystals and other elements of winter, Ingo features the clean design of mouth blown German art glass for an elegant statement.

FEATURES

- All socket sets include 6ft wire that may be cut in the field
- Lamp included
- Free of projected heat, ultraviolet and infrared radiation
- 5 year warranty

SPECIFICATIONS

Construction	Mouth blown glass shade with plated metal hardware, Mouth blown glass shade with electroplated metal hardware
Input:	12 VAC, 50/60Hz
Dimming:	ELV: 100-15%
Light Source:	LED Bi-Pin 2.7W, 110lm, 3000K, 85CRI, Xenon Bi-Pin Max 50W
Rated Life:	50,000 Hours
Finish:	Clear Frosted/Chrome, Clear Frosted/Brushed Nickel
Operating Temp:	-4°F to 104°F (-20°C to 40°C)
Standards:	UL, cUL, Dry Location Listed



FINISHES:



Clear Frosted/Brushed Nickel Clear Frosted/Chrome

WAC LIGHTING

Clarity

Quick Connect™ Pendant 3000K

Model & Wattage	Lumens	Color Temp & CRI	Finish
QP-LED916 QP916	330		CL/BN Clear/Brushed Nickel CL/CH Clear/Chrome

Fixture Type: _____
Catalog Number: _____
Project: _____
Location: _____

Example: **QP-LED916-CL/BN**

DESCRIPTION

Lovingly created by hand by Germany's finest glass blowers, the Clarity art glass pendant demonstrates dazzling spectral properties and can be mounted for use on track, rail or canopies.

FEATURES

- All socket sets include 6ft wire that may be cut in the field
- Lamp included
- Free of projected heat, ultraviolet and infrared radiation
- 5 year warranty

SPECIFICATIONS

Construction	Mouth blown glass shade with electroplated metal hardware, Mouth blown glass shade with plated metal hardware
Input:	12 VAC,50/60Hz
Dimming:	ELV: 100-15%
Light Source:	Xenon Bi-Pin Max 50W, Integrated LED 4W, 330lm, 3000K, 85CRI
Rated Life:	50,000 Hours
Finish:	Clear/Brushed Nickel, Clear/Chrome
Operating Temp:	-4°F to 104°F (-20°C to 40°C)
Standards:	UL, cUL, Dry Location Listed



FINISHES:



Clear/Brushed Nickel



Clear/Chrome

WAC LIGHTING

Bullet

Quick Connect™ Pendant 3000K

Model & Wattage	Lumens	Color Temp & CRI	Finish
QP-LED966 QP966	330		BN/BN Brushed Nickel CH/CH Chrome

Fixture Type: _____
Catalog Number: _____
Project: _____
Location: _____

Example: **QP-LED966-BN/BN**

DESCRIPTION

Modern minimalist form derived from function, Bullet pendants are available in two hardware matching metal finishes. The white interior of the shade reflects light onto the surface below.

FEATURES

- All socket sets include 6ft wire that may be cut in the field
- Lamp included
- Free of projected heat, ultraviolet and infrared radiation
- 5 year warranty

SPECIFICATIONS

Construction	Aluminum Shade with electroplated metal hardware, Aluminum Shade with plated metal hardware
Input:	12 VAC,50/60Hz
Dimming:	ELV: 100-15%
Light Source:	Xenon Bi-Pin Max 50W, Integrated LED 6.4W, 450lm, 3000K, 85 CRI
Rated Life:	50,000 Hours
Finish:	Brushed Nickel, Chrome
Operating Temp:	-4°F to 104°F (-20°C to 40°C)
Standards:	UL, cUL, Dry Location Listed



FINISHES:

