

# WAC LIGHTING

## Solorail™

### Rod Coupler

Model	Finish
LM-RI	BN Brushed Nickel

Example: **LM-RI-BN**

#### DESCRIPTION

WAC Lighting low voltage Monorail can be shaped in the field and designed to navigate curves for custom designs. The versatile Solorail™ accommodates hundreds of Quick Connect™ pendants and fixtures. Designed with the thinnest profile in the industry, Solorail™ is engineered for rigorous use in commercial, hospitality and retail applications. Featuring electroplated solid copper bars and precision fabricated components, with a maximum capacity of 25 amperes or 600 watts at 12 volts and 600 watts at 24 volts.

#### FEATURES

- Dimensions: Dia. 3/8" x 7/8" Length
- Use two per power feed, four per dual power feed, one additional coupler per rod needed when joining two rods in excess of 48".
- 5 year warranty

#### SPECIFICATIONS

<b>Dimming:</b>	N/T
<b>Finish:</b>	Electroplated Brushed Nickel
<b>Operating Temp:</b>	-4°F to 104°F (-20°C to 40°C)
<b>Standards:</b>	UL, cUL, Dry Location Listed

Fixture Type: \_\_\_\_\_  
Catalog Number: \_\_\_\_\_  
Project: \_\_\_\_\_  
Location: \_\_\_\_\_



#### FINISHES:



Brushed  
Nickel

# WAC LIGHTING

## Solorail™

### Extension Rods

Model	Finish
LM-R12 LM-R24 LM-R36	BN Brushed Nickel

Fixture Type: \_\_\_\_\_  
Catalog Number: \_\_\_\_\_  
Project: \_\_\_\_\_  
Location: \_\_\_\_\_

Example: **LM-R12-BN**

#### DESCRIPTION

WAC Lighting low voltage Monorail can be shaped in the field and designed to navigate curves for custom designs. The versatile Solorail™ accommodates hundreds of Quick Connect™ pendants and fixtures. Designed with the thinnest profile in the industry, Solorail™ is engineered for rigorous use in commercial, hospitality and retail applications. Featuring electroplated solid copper bars and precision fabricated components, with a maximum capacity of 25 amperes or 600 watts at 12 volts and 600 watts at 24 volts.

#### FEATURES

- Use with standoffs and power feeds
- Use two per circuit with rod couplers to extend power feeds
- Field cut to size and join with rod couplers
- 5 year warranty

#### SPECIFICATIONS

<b>Dimming:</b>	N/T
<b>Finish:</b>	Electroplated Brushed Nickel
<b>Operating Temp:</b>	-4°F to 104°F (-20°C to 40°C)
<b>Standards:</b>	UL, cUL, Dry Location Listed



#### FINISHES:



Brushed  
Nickel