

Solorail™

300W 24V Integrated Magnetic Transformer

Model	Finish
LM-EN24-300M	BN Brushed Nickel

Example: **LM-EN24-300M-BN**

DESCRIPTION

Surface mount magnetic low voltage transformer for the WAC Solorail™ system. The canopy style enclosure includes the transformer and the track power feed adapter. The standoff height can be increased by the use of two LM-R extension rods.

FEATURES

- 8 7/8" canopy
- Use with 5 3/4" (LM-X5) standoff
- Voltage drop at run length 50'
- 300W maximum load
- Dims with magnetic low voltage dimmers
- Output circuit breaker located on the upper lip of the canopy enclosure is a magnetic push to reset type
- Contains integral de-buzzing coil
- The surface mount canopy transformer is an ideal choice when the installation is on an existing ceiling
- Transformer included
- 5 year warranty

SPECIFICATIONS

Input:	120 VAC, 60Hz
Dimming:	N/T
Mounting:	Installs to a standard junction box. Total weight = 11 lbs. The standard LM-EN24-300M configuration matches the height of the 5 3/4" (LM-X5) standoffs.
Finish:	Electroplated Brushed Nickel
Operating Temp:	-4°F to 104°F (-20°C to 40°C)
Standards:	UL, cUL, Dry Location Listed

Fixture Type: _____
Catalog Number: _____
Project: _____
Location: _____




FINISHES:



Brushed Nickel

LINE DRAWING:



Solorail™

300W 24V Integrated Magnetic Transformer

Fixture Type: _____
Catalog Number: _____
Project: _____
Location: _____

ACCESSORIES

	<i>Model</i>	<i>Description</i>	<i>Finish</i>
	LM-R36-BN	Solorail™	Brushed Nickel
	LM-R24-BN	Solorail™	Brushed Nickel
	LM-R12-BN	Solorail™	Brushed Nickel