Fixture Type:

Catalog Number:

Project:

Location:

WAC LIGHTING

Straitaway

Bath & Wall 4CCT

Model & Size	Color Temp	Finish	LED Watts	LED Lumens	Delivered Lumens
❍ WS-51524 24"	❍ 2700K ❍ 3000K ❍ 3500K ❍ 4000K	❍ BK Black ❍ BN Brushed Nickel	18.5W	1665	916

Example: **WS-51524-40-BN**
For custom requests please contact customs@waclighting.com

DESCRIPTION

Clean and Simple. A rounded linear silhouette features and white diffuser adorned with triangular end caps and square backplate designed to provide abundant and balanced light through an understated aesthetic.

FEATURES

• Built in color temperature adjustability. Switch from 2700K/3000K/3500K/4000K
• Option to pre-select color temperature or adjust in the field
• Decorative conversion plate to accommodate standard 4" junction box is included
• Driver included
• 5 Year warranty

SPECIFICATIONS

Color Temp:	2700K,3000K,3500K,4000K
Input:	120/277V,50/60Hz
CRI	90
Dimming:	ELV: 100-10% , TRIAC: 100-10%
Rated Life:	50,000 Hours
Mounting:	Can be mounted on wall in all orientations
Standards:	ETL, cETL, Title 24 JA8 Compliant, ADA, Damp Location Listed
Construction	Aluminum hardware with acrylic diffuser

FINISHES:

Black | Brushed Nickel

LINE DRAWING



WS-51524

Fixture Type:

Catalog Number:

Project:

Location:

WAC LIGHTING

Straitaway

Bath & Wall 4CCT

Model & Size	Color Temp	Finish	LED Watts	LED Lumens	Delivered Lumens
❍ WS-51532 32"	❍ 2700K ❍ 3000K ❍ 3500K ❍ 4000K	❍ BK Black ❍ BN Brushed Nickel	24.5W	2205	1213

Example: **WS-51532-40-BN**
For custom requests please contact customs@waclighting.com

DESCRIPTION

Clean and Simple. A rounded linear silhouette features and white diffuser adorned with triangular end caps and square backplate designed to provide abundant and balanced light through an understated aesthetic.

FEATURES

• Built in color temperature adjustability. Switch from 2700K/3000K/3500K/4000K
• Option to pre-select color temperature or adjust in the field
• Decorative conversion plate to accommodate standard 4" junction box is included
• Driver included
• 5 Year warranty

SPECIFICATIONS

Color Temp:	2700K,3000K,3500K,4000K
Input:	120/277V,50/60Hz
CRI	90
Dimming:	ELV: 100-10% , TRIAC: 100-10%
Rated Life:	50,000 Hours
Mounting:	Can be mounted on wall in all orientations
Standards:	ETL, cETL, Title 24 JA8 Compliant, ADA, Damp Location Listed
Construction	Aluminum hardware with acrylic diffuser

FINISHES:

Black | Brushed Nickel

LINE DRAWING



WS-51532