

Fixture Type: _____
 Catalog Number: _____
 Project: _____
 Location: _____

Tulum

Quick Connect™ Pendant 3000K

Model & Wattage	Lumens	Color Temp & CRI	Finish
QP-914LED QP914	235		FR/BN Frosted/Brushed Nickel FR/CH Frosted/Chrome

Example: **QP-914LED-FR/BN**

DESCRIPTION

A frosted glass pendant carefully etched and paneled to reveal the mini pendant's inner light, Tulum offers a visually soft option for a contemporary space using a modern design that is perfect above a counter, bar or table.

FEATURES


- All socket sets include 6ft wire that may be cut in the field
- Lamp included
- Free of projected heat, ultraviolet and infrared radiation
- 5 year warranty

SPECIFICATIONS

Construction	Mouth blown glass shade with plated metal hardware, Mouth blown glass shade with electroplated metal hardware
Input:	12 VAC, 50/60Hz
Dimming:	ELV: 100-15%
Light Source:	LED Bi-Pin 2.7W, 110lm, 3000K, 85CRI, Xenon Bi-Pin Max 50W
Rated Life:	50,000 Hours
Finish:	Frosted/Chrome, Frosted/Brushed Nickel
Operating Temp:	-4°F to 104°F (-20°C to 40°C)
Standards:	UL, cUL, Dry Location Listed



FINISHES:



Quick Connect™

1 Point Round Mirrored Canopy

Model & Product

QMP-G1RN-MR 1-Point round mirrored canopy

Example: **QMP-G1RN-MR**

FEATURES

- For use with any of our Quick Connect™ pendants
- 60W integral electronic transformer included
- Smooth and continuous ELV dimming
- Includes accent caps in Brushed Nickel and Chrome to match any of our socket sets
- 5 year warranty

SPECIFICATIONS

Construction	Mirrored Canopy with plated hardware
Power:	Max 60W
Input:	120 VAC,50/60Hz
Standards:	UL, cUL, Dry Location Listed

Fixture Type: _____

Catalog Number: _____

Project: _____

Location: _____



Quick Connect™

3 Points Rectangular Mirrored Canopy

Model & Product

QMP-G3RE-MR 3-Point rectangular mirrored canopy

Fixture Type: _____

Catalog Number: _____

Project: _____

Location: _____

Example: **QMP-G3RE-MR**

FEATURES

- For use with any of our Quick Connect™ pendants
- 60W integral electronic transformer for each drop
- Smooth and continuous ELV dimming
- Includes accent caps in Brushed Nickel and Chrome to match any of our socket sets
- 5 year warranty

SPECIFICATIONS

Construction	Mirrored Canopy with plated hardware
Power:	Max 3 X 60W
Input:	120 VAC,50/60Hz
Standards:	UL, cUL, Dry Location Listed

