

Fixture Type: _____
 Catalog Number: _____
 Project: _____
 Location: _____

Twist-N-Lite Pendant

Model & Size	Color Temp & CRI	Watt	Lumens	Finish
PD-250905	CS 2700K/3000K/3500K/4000K/5000K - 90	12W	850	BK Black BN Brushed Nickel WT White

Example: **PD-250905-CS-BK**

DESCRIPTION

Quick and convenient. Easy to use and easy to install, our new Twist-N-Lite system offers a variety of surface mounts and pendant luminaires in five color temperatures and three finishes. A single flexible mounting base accommodates our complete suite of Twist-N-Lite products. The flexible design enables you to interchange the fixtures in the field to meet your various lighting applications. This energy-efficient engineering wonder offers dimmable options for high performance and a classic, minimalistic aesthetic. Select your color temperature, Twist it in and Turn it on. Elevating multifunctional illumination to a higher standard.

FEATURES

- Mount and power any fixture in the Twist-N-Lite family by twisting it onto the canopy
- All wiring and connections are made in the junction box prior to installing the mounting base and canopy
- Shared canopy allows for easily swapping between fixtures without adjusting the mounting hardware
- 5-CCT Switchable between 2700K and 5000K
- Dual-layer acrylic for frosted and even glow
- Retract or extend the cable by pressing on the cable gripper
- Driver concealed within the fixture
- 5 year warranty

SPECIFICATIONS

Construction	Aluminum with dual-layer acrylic diffuser
Power:	12W
Input:	120 VAC, 50/60Hz
Dimming:	ELV: 100-10% , TRIAC: 100-10%
Light Source:	Integrated LED
Lens:	Dual-layer acrylic diffuser
Rated Life:	50,000 Hours
Mounting:	Installs over a 3", 4" or 3/0-4/0 hybrid junction box
Finish:	Electrostatically Powder Coated: White, Electroplated Brushed Nickel, Black
Operating Temp:	-4°F to 104°F (-20°C to 40°C)
Standards:	ETL, cETL, Damp Location Listed, Title 24 JA8 Compliant



FINISHES:

