


WALL WASH 120V

5022

WAC

LANDSCAPE LIGHTING



Fixture Type:

Catalog Number:

Project: _____

Location: _____

PRODUCT DESCRIPTION

Landscape Wall Wash luminaire

FEATURES

- A uniform wide distribution wall wash from a small form factor
- Integral dimmer
- IP66 rated, Protected against high-pressure water jets
- Solid diecast brass or corrosion resistant aluminum
- Factory sealed water tight fixtures
- 6' lead wire and wire nuts included
- Maintains constant lumen output against voltage drop
- UL 1598 Listed
- Not suitable to use with external dimmers

SPECIFICATIONS

- Input:** 110V - 120VAC
Power: 3.5W to 14.5W (Use VA value for sizing the transformer and calculate voltage drop.)
Brightness: 95 lm to 855 lm
Beam Angle: 15° upward (50° by 80°)
CRI: 85
Rated Life: 45,000 hours

ORDERING NUMBER

		Color Temp	Finish
5022	Wall wash 120V	30 3000K	BK Black on Aluminum BZ Bronze on Aluminum BBR Bronze on Brass

5022-30 _____

Example: **5022-30BBR**

wacighting.com

Phone (800) 526.2588

Fax (800) 526.2585

Headquarters, East Manufacturing Facility

44 Harbor Park Drive

Port Washington, NY 11050

South East Manufacturing Facility

1600 Distribution Ct

Lithia Springs, GA 30122

Central Manufacturing Facility

1700 South J Elmer Freeway, Ste 100

Cedar Hill, TX 75104

West Manufacturing Facility






1750 S Archibald Ave

Ontario, CA 91761

WAC

LANDSCAPE LIGHTING

Accessories

Power Stake		M6000-STAKE	PVC			Easy wiring accessory designed for 12V & 120V products. Eliminates the need for a separate Junction box.
Tree Mount Junction Box		5000-TCP-BZ 5000-TCP-BK	Bronze on Aluminum Black on Aluminum			Bronze on Aluminum box with Stainless steel mounting screws. Two ½" NPT threaded holes
Optics		LENS-2X4-AMB LENS-2X4-GRN LENS-2X4-RED	Amber Green Red	LENS-2X4-BLU LENS-2X4-FR LENS-2X4-SPR	Blue Frosted Spread	Enhances saturation of florals and foliage
Extension Rods		5000-X04-BZ 5000-X04-BK 5000-X04-BBR 5000-X08-BZ 5000-X08-BK 5000-X08-BBR 5000-X12-BZ 5000-X12-BK 5000-X12-BBR	4 in 4 in 4 in 8 in 8 in 8 in 12 in 12 in 12 in	5000-X18-BZ 5000-X18-BK 5000-X18-BBR 5000-X24-BZ 5000-X24-BK 5000-X24-BBR	18 in 18 in 18 in 24 in 24 in 24 in	Extends distance between Accent light and Surface Mount Canopy, Stake, or Tree Mount box
Rod L-Coupler		5000-LCO-BZ	Bronze			

Magnetic Transformers

Stainless Steel, 12-15V output, IP65 rated, UL 1838 listed
See transformer spec sheet for details and its accessories

9075-TRN-SS
75W Max

9150-TRN-SS
150W Max

9300-TRN-SS
300W Max

9600-TRN-SS
600W Max



wacighting.com

Phone (800) 526.2588
Fax (800) 526.2585

Headquarters, East Manufacturing Facility
44 Harbor Park Drive
Port Washington, NY 11050

South East Manufacturing Facility
1600 Distribution Ct
Lithia Springs, GA 30122

Central Manufacturing Facility
1700 South J Elmer Freeway, Ste 100
Cedar Hill, TX 75104

West Manufacturing Facility
1750 S Archibald Ave
Ontario, CA 91761