


MINI ACCENT 12V

5111

WAC

LANDSCAPE LIGHTING



Fixture Type:

Catalog Number:

Project: _____

Location: _____

PRODUCT DESCRIPTION

Landscape mini accent luminaire. One fixture replaces all older halogen landscape accent lights

FEATURES

- Continuously Adjustable Beam Angles. Indexed at 10°, 25°, 40°, 50°
- Continuously Adjustable brightness control. Indexed at 1W, 2W, 4W, 6W, 7W
- IP66 rated, Protected against high-pressure water jets
- Solid diecast brass or corrosion resistant aluminum
- Factory sealed water tight fixtures
- Constant output for 9V-15V input
- Can be used as an uplight or downlight
- 2700K or 3000K color temperature
- Mounting stake, detachable shroud, 6' lead wire and direct burial gel filled wire nuts included
- MLV dimmable with remote MLV dimmers

SPECIFICATIONS

- Input:** 9-15VAC
- Power:** 1W to 7W / 2VA -10.5VA (Use VA value for sizing the transformer and calculate voltage drop.)
- Brightness:** 45 lm to 365 lm
- Beam Angle:** 10° to 50°
- CRI:** 85
- Rated Life:** 70,000 hours

ORDERING NUMBER

| | | Color Temp | Finish |
|------|-----------------|------------|------------------------------|
| 5111 | Mini Accent 12V | 27 | 2700K Warm White |
| | | 30 | 3000K Pure White |
| | | | |
| | | | BK Black on Aluminum |
| | | | BZ Bronze on Aluminum |
| | | | BBR Bronze on Brass |
| | | | WT White on Aluminum |

5111-30_____

Example: 5111-30BBR

wacighting.com

Phone (800) 526.2588

Fax (800) 526.2585

Headquarters, East Manufacturing Facility

44 Harbor Park Drive

Port Washington, NY 11050

South East Manufacturing Facility

1600 Distribution Ct

Lithia Springs, GA 30122

Central Manufacturing Facility

1700 South J Elmer Freeway, Ste 100

Cedar Hill, TX 75104

West Manufacturing Facility

1750 S Archibald Ave

Ontario, CA 91761











MINI ACCENT 12V

5111

WAC

LANDSCAPE LIGHTING

Accessories

| | | | | | | |
|----------------------------|--|--|--|---|----------------------------------|--|
| Accent Snoot |  | 5111-SNOOT-BK 5111-SNOOT-BZ 5111-SNOOT-BBR | Black on Aluminum Bronze on Aluminum Bronze on Brass | Shields lamp and reduces glare | | |
| 5" Long Shroud |  | 5111-LSHR-BK 5111-LSHR-BZ 5111-LSHR-BBR | Black on Aluminum Bronze on Aluminum Bronze on Brass | Reduce glare. Ideal for downlighting application | | |
| Additional Stake |  | 9000-ST9-BZ | Bronze | Durable PVC stake | | |
| Surface Mount Flange/Stake |  | 5000-SCP-BZ 5000-SCP-BBR 5000-SCP-BK | Bronze on Aluminum Bronze on Brass Black on Aluminum | Includes three 7 inch threaded stainless steel stabilizing pins for ground mounting or surface mounts with four screws or over a junction box | | |
| Guardian Mount |  | 9000-SP9-BZ | Stainless Steel | Heavy duty stainless steel spike to position fixture Formed from a single piece of metal | | |
| Gutter Mount Bracket |  | 5000-GM-BZ 5000-GM-BK | Stainless Steel | Stainless Steel universal mounting bracket for gutter mounting fixture | | |
| Tree Mount Junction Box |  | 5000-TCP-BZ 5000-TCP-BK | Bronze on Aluminum Black on Aluminum | Bronze on Aluminum box with Stainless steel mounting screws. Two 1/2" NPT threaded holes | | |
| Optics |  | LENS-16-AMB LENS-16-GRN LENS-16-RED LENS-16-BLU | Amber Green Red Blue | LENS-16-FR LENS-16-SPR LENS-16-BEL | Frosted Spread Elongating | Enhances saturation of florals and foliage |
| Extension Rods |  | 5000-X04-BZ 5000-X04-BK 5000-X08-BZ 5000-X08-BK 5000-X12-BZ 5000-X12-BK | 4 in 4 in 8 in 8 in 12 in 12 in | 5000-X18-BZ 5000-X18-BK 5000-X24-BZ 5000-X24-BK | 18 in 18 in 24 in 24 in | Extends distance between Accent light and Surface Mount Canopy, Stake, or Tree Mount box |
| Rod L-Coupler |  | 5000-LCO-BZ | Bronze | | | |

Magnetic Transformers

Stainless Steel, 12-15V output, IP65 rated, UL 1838 listed
See transformer spec sheet for details and its accessories

9075-TRN-SS
75W Max

9150-TRN-SS
150W Max

9300-TRN-SS
300W Max

9600-TRN-SS
600W Max



wacighting.com
Phone (800) 526.2588
Fax (800) 526.2585

Headquarters, East Manufacturing Facility
44 Harbor Park Drive
Port Washington, NY 11050

South East Manufacturing Facility
1600 Distribution Ct
Lithia Springs, GA 30122

Central Manufacturing Facility
1700 South J Elmer Freeway, Ste 100
Cedar Hill, TX 75104

West Manufacturing Facility
1750 S Archibald Ave
Ontario, CA 91761