

GATE LED BOLLARD/PATH

6651

WAC

LANDSCAPE LIGHTING



Shown without plate



Shown with plate



Fixture Type:

Catalog Number:

Project: _____

Location: _____

PRODUCT DESCRIPTION

Sleek linear design blends seamlessly into pathways while providing soft, even illumination

FEATURES

- IP66 rated, Protected against powerful water jets
- Factory sealed water tight fixtures
- Corrosion resistant aluminum alloy
- Recommended spacing for installation: Residential: 7 to 9ft; Commercial: 5 to 7ft
- Mounting stake, 6 foot lead wire, and detachable back plate included
- UL & cUL 1838 Listed

SPECIFICATIONS

Input: 9-15VAC (Transformer is required)
Power: 7W / 7.5VA (Use VA value for sizing the transformer and calculate voltage drop.)
Brightness: Up to 115 lm
CRI: 90
Rated Life: 60,000 hours

Mounting accessory included



ORDERING NUMBER

	Color Temp	Finish
6651 Canopy	27 2700K Warm White	BZ Bronze on Aluminum
	30 3000K Pure White	BK Black on Aluminum

6651-___BK

Example: **6651-30BK**

wacighting.com

Phone (800) 526.2588

Fax (800) 526.2585

Headquarters, East Manufacturing Facility

44 Harbor Park Drive

Port Washington, NY 11050

South East Manufacturing Facility

1600 Distribution Ct

Lithia Springs, GA 30122

Central Manufacturing Facility

1700 South J Elmer Freeway, Ste 100

Cedar Hill, TX 75104

West Manufacturing Facility

1750 S Archibald Ave

Ontario, CA 91761