


CUBE ARCHITECTURAL DC-PD05

WAC LIGHTING

LED Pendant Mounts



24"

Extension rod for additional length up to 96"

DS-PDX24

Fixture Type:

Catalog Number:

Project: _____

Location: _____

PRODUCT DESCRIPTION

The latest energy efficient LED technology in an appealing cubical profile delivers accent and wall wash lighting. Comes in various light distribution and beam angle options.

FEATURES

- High performance exterior rated LED pendant
- Includes 45° swivel canopy and 2 field cuttable 24" rods
- Solid aluminum construction
- 5 year warranty

SPECIFICATIONS

- Input:** Universal voltage 120V - 277VAC, 50/60Hz
- Dimming:** Electronic low voltage (ELV) : 100% - 5%
0-10V: 100% - 1%
- Light Source:** High output 3 Step Mac Adam Ellipse COB
Rated life of 60,000 hours at L70
- Finish:** Electrostatically powder coated, white, black, bronze and graphite
- Standards:** IP65 rated, UL & cUL wet location listed
Energy Star® 2.2 rated Title 24 JA8-2016 Compliant

ORDERING NUMBER

Diameter	Watt	Beam	Beam Angle	Color	Temp	Reference Output ¹			Efficacy	Light Distribution	Finish
						CRI	Lumen	CBCP	(Lm/W)		
	DC-PD05	S Spot	16°	927	2700K	90	1825	10050	73		BK Black WT White BZ Bronze GH Graphite
				827	2700K	85	2090	12057	88		
				930	3000K	90	1895	10427	76		
				830	3000K	85	2300	12644	92		
				835	3500K	85	2350	12937	94		
	840	4000K	85	2375	13062	95					
	DC-PD0517	N Narrow	25°	927	2700K	90	1810	5280	72		
				827	2700K	85	2170	6335	87		
				930	3000K	90	1880	5478	75		
				830	3000K	85	2275	6643	91		
				835	3500K	85	2330	6797	93		
	840	4000K	85	2350	6863	94					
	DC-PD0517	F Flood	33°	927	2700K	90	1900	4515	76		
				827	2700K	85	2280	5417	91		
				930	3000K	90	1970	4685	79		
830				3000K	85	2390	5681	96			
835				3500K	85	2445	5812	98			
840	4000K	85	2470	5870	99						

¹Reference output shows 25W output. Multiply by 0.7 to determine output for 17W combinations.

DC-PD05-_____ - _____

Example: **DC-PD05-S930-GH**


wacighting.com
Phone (800) 526.2588
Fax (800) 526.2585

Headquarters/Eastern Distribution Center
44 Harbor Park Drive
Port Washington, NY 11050

Central Distribution Center
1600 Distribution Ct
Lithia Springs, GA 30122

Western Distribution Center
1750 Archibald Avenue
Ontario, CA 91760

MOUNTING ACCESSORIES

	<i>Extension Rod</i>	DS-PDX24	<i>One 24" extension rod for DC-PDSK Can be field cut</i>	Finish	
				BK <i>Black</i>	
				WT <i>White</i>	
				BZ <i>Bronze</i>	
				GH <i>Graphite</i>	

Example: **DS-PDX24-WT**