


LED Wall Mounts



Fixture Type:

Catalog Number:

Project:

Location:

PRODUCT DESCRIPTION

The latest energy efficient LED technology in an appealing cubical profile delivers accent and wall wash lighting. Comes in various light distribution and beam angle options.

FEATURES

- Single light extended body high performance exterior rated LED wall mount
- Fixture can install upside down to alter light distribution
- Solid aluminum construction
- 5 year warranty

SPECIFICATIONS

- Input:** Universal voltage 120V - 277VAC, 50/60Hz
- Dimming:** Electronic low voltage (ELV) : 100% - 5%
0-10V: 100% - 1%
- Light Source:** High output 3 Step Mac Adam Ellipse COB
Rated life of 60,000 hours at L70
- Finish:** Electrostatically powder coated, white, black, bronze and graphite
- Standards:** IP65 rated, UL & cUL wet location listed, Energy Star® 2.2 rated Title 24 JA8-2016 Compliant
- Operating Temp:** -13°F to 122°F (-25°C to 50°C)

ORDERING NUMBER

Diameter	Watt	Beam	Beam Angle	Color Temp	CRI	Reference Output ¹ Lumen	CBCP	Efficacy (lm/w)	Light Distribution	Finish	
DC-WE05	5"	S Straight up or down	16°	927S	2700K	90	1825	10050	73		BK Black WT White BZ Bronze GH Graphite
				827S	2700K	85	2190	12057	88		
				930S	3000K	90	1895	10427	76		
				830S	3000K	85	2300	12644	92		
				835S	3500K	85	2350	12937	94		
				840S	4000K	85	2375	13062	95		
		N Straight up or down	25°	927S	2700K	90	1810	5280	72		
				827S	2700K	85	2170	6335	87		
				930S	3000K	90	1880	5478	75		
				830S	3000K	85	2275	6643	91		
				835S	3500K	85	2330	6797	93		
		F Straight up or down	33°	927S	2700K	90	1900	4515	76		
				827S	2700K	85	2280	5417	91		
				930S	3000K	90	1970	4685	79		
				830S	3000K	85	2390	5681	96		
835S	3500K			85	2445	5812	98				
DC-WE0517	5"	F Away from the wall	N/A	927A	2700K	90	2000		80		
				827A	2700K	85	2400		96		
				930A	3000K	90	2075	N/A	83		
				830A	3000K	85	2520		101		
				835A	3500K	85	2575		103		
		F Towards the wall	N/A	927B	2700K	90	2000		80		
				827B	2700K	85	2400		96		
				930B	3000K	90	2075	N/A	83		
				830B	3000K	85	2520		101		
				835B	3500K	85	2575		103		
840B	4000K	85	2600		104						

DC-WE05- _____ - _____ ¹Reference output shows 25W output. Multiply by 0.7 to determine output for 17W combinations.

Example: DC-WE05-F930A-WT

wacighting.com
Phone (800) 526.2588
Fax (800) 526.2585

Headquarters/Eastern Distribution Center
44 Harbor Park Drive
Port Washington, NY 11050

Central Distribution Center
1600 Distribution Ct
Lithia Springs, GA 30122

Western Distribution Center
1750 Archibald Avenue
Ontario, CA 91760