TUBE ARCHITECTURAL DS-WE05

LED Wall Mounts

WAC LIGHTING®



Fixture Type: _____

Catalog Number: _____

Project: _____

Location: _____

PRODUCT DESCRIPTION

The latest energy efficient LED technology in an appealing cylindrical profile delivers accent and wall wash lighting. Comes in various light distribution and beam angle options.

FEATURES

- Single light extended body high performance exterior rated LED wall mount
- Fixture can install upside down to alter light distribution
- Solid aluminum construction
- 5 year warranty

SPECIFICATIONS

Input:	Universal voltage 120V - 277VAC, 50/60Hz
Dimming:	Electronic low voltage (ELV) : 100% - 5% 0-10V: 100% - 1%
Light Source:	High output 3 Step Mac Adam Ellipse COB Rated life of 60,000 hours at L70
Finish:	Electrostatically powder coated, white, black,
Standards:	bronze and graphite
Operating Temp:	IP65 rated, ETL & cETL wet location listed, Title 24 JA8 Compliant -13°F to 122°F (-25°C to 50°C)

ORDERING NUMBER

Diameter		Watt	Beam	Beam Angle	Color	Temp	CRI	Reference Lumen	Output [1] CBCP	Efficacy (lm/w)	Light Distribution
DS-WD05 **DS-WE0517**	5″	25W 17 W	**S** *Straight up and down*	16°	**927S**	2700K	90	1825	10050	73	
					27S	2700K	85	2190	12057	88	
					930S	3000K	90	1895	10427	76	
					30S	3000K	85	2300	12644	92	
					35S	3500K	85	2350	12937	94	
					40S	4000K	85	2375	13062	95	
			N *Straight up and down*	25°	**927S**	2700K	90	1810	5280	72	
					27S	2700K	85	2170	6335	87	
					930S	3000K	90	1880	5478	75	
					30S	3000K	85	2275	6643	91	
					35S	3500K	85	2330	6797	93	
					40S	4000K	85	2350	6863	94	
			F *Straight up and down*	33°	**927S**	2700K	90	1900	4515	76	
					27S	2700K	85	2280	5417	91	
					930S	3000K	90	1970	4685	79	
					30S	3000K	85	2390	5681	96	
					35S	3500K	85	2445	5812	98	
					40S	4000K	85	2470	5870	99	
			F *Away from the wall*	N/A	**927A**	2700K	90	2000	N/A	80	
					27A	2700K	85	2400		96	
					930A	3000K	90	2075		83	
					30A	3000K	85	2520		101	
					35A	3500K	85	2575		103	
					40A	4000K	85	2600		104	
			F *Towards the wall*	N/A	**927B**	2700K	90	2000	N/A	80	
					27B	2700K	85	2400		96	
					930B	3000K	90	2075		83	
					30B	3000K	85	2520		101	
					35B	3500K	85	2575		103	
					40B	4000K	85	2600		104	

Finish

BK *Black*
WT *White*
BZ *Bronze*
GH *Graphite*

DS-WE05-_____-____

Example: **DS-WE05-F930A-WT**

[1] Reference output shows 25W output. Multiply by 0.7 to determine output for 17W combinations.

waclighting.com
Phone (800) 526.2588
Fax (800) 526.2585

Headquarters, East Manufacturing Facility
44 Harbor Park Drive
Port Washington, NY 11050

South East Manufacturing Facility
1600 Distribution Ct
Lithia Springs, GA 30122

Central Manufacturing Facility
1700 South J Elmer Freeway, Ste 100
Cedar Hill, TX 75104

West Manufacturing Facility
1750 S Archibald Ave
Ontario, CA 91761

WAC Lighting retains the right to modify the design of our products at any time as part of the company's continuous improvement program.