


TUBE ARCHITECTURAL DS-WS08

WAC LIGHTING

LED Wall Mounts



Fixture Type:

Catalog Number:

Project:

Location:

PRODUCT DESCRIPTION

The latest energy efficient LED technology in an appealing cylindrical profile delivers accent and wall wash lighting. Comes in various light distribution and beam angle options.

FEATURES

- High performance exterior rated LED wall mount light
- Fixture can install upside down to alter light distribution
- Solid aluminum construction
- 5 year warranty

SPECIFICATIONS

Input:	Universal voltage 120V - 277VAC, 50/60Hz
Dimming:	Electronic low voltage (ELV) : 100% - 5% 0-10V: 100% - 1%
Light Source:	High output 3 Step Mac Adam Ellipse COB Rated life of 60,000 hours at L70
Finish:	Electrostatically powder coated, white, black, bronze and graphite
Standards:	IP65 rated, ETL & cETL wet location listed, Energy Star® 2.2 rated Title 24 JA8-2016 Compliant
Operating Temp:	-13°F to 122°F (-25°C to 50°C)

ORDERING NUMBER

Diameter	Watt	Beam	Angle	Color Temp	CRI	Reference Lumen	Output ¹ CBCP	Efficacy (lm/w)	Light Distribution	Finish	
DS-WS08	8" 46W	S Straight up or down	18°	927S	2700K	90	3080	15187	67		BK Black WT White BZ Bronze GH Graphite
				27S	2700K	85	3865	19064	84		
				930S	3000K	90	3275	16156	71		
				30S	3000K	85	3935	19387	86		
				35S	3500K	85	4030	19872	88		
				40S	4000K	85	4095	20195	89		
		N Straight up or down	25°	927S	2700K	90	3185	10536	68		
				27S	2700K	85	4000	13226	87		
				930S	3000K	90	3390	11208	74		
				30S	3000K	85	4070	13450	88		
				35S	3500K	85	4170	13786	91		
				40S	4000K	85	4240	14010	92		
		F Straight up or down	35°	927S	2700K	90	3015	5475	66		
				27S	2700K	85	3785	7211	82		
				930S	3000K	90	3210	6111	70		
				30S	3000K	85	3850	7334	84		
				35S	3500K	85	3945	7517	86		
				40S	4000K	85	4010	7639	87		
F Away from the wall	N/A	927A	2700K	90	3020		66				
		27A	2700K	85	3790		82				
		930A	3000K	90	3210	N/A	70				
		30A	3000K	85	3855		84				
		35A	3500K	85	3950		86				
		40A	4000K	85	4015		87				
F Towards the wall	N/A	927B	2700K	90	3020		66				
		27B	2700K	85	3790		82				
		930B	3000K	90	3210	N/A	70				
		30B	3000K	85	3855		84				
		35B	3500K	85	3950		86				
		40B	4000K	85	4015		87				

DS-WS08-_____ - _____

¹Reference output shows 46W output. Multiply by 0.8 to determine output for 34W combinations.

Example: DS-WS08-F930A-WT

waclighting.com
Phone (800) 526.2588
Fax (800) 526.2585

Headquarters/Eastern Distribution Center
44 Harbor Park Drive
Port Washington, NY 11050

Central Distribution Center
1600 Distribution Ct
Lithia Springs, GA 30122

Western Distribution Center
1750 Archibald Avenue
Ontario, CA 91760