


STEALTH SILO – MR-2007

Remote Driver Monopoint Luminaire

WAC



Fixture Type:

Catalog Number:


Project:

Location:

ADJUSTABLE 15° - 50°



15°



50°

PRODUCT DESCRIPTION

Silo offers superior light output with a wide range of dynamic beam adjustment in a small, sleek design. Engineered synthesis of driver, single point source LED, optical and thermal management in a slender die-cast housing. Ideal for residential, retail and lower mounting height commercial applications.

FEATURES

- Construction: Die-cast aluminum with rotatable front face
- Continuously adjustable beam angle between 15° - 50°
- Stealth armature with 360° horizontal rotation and 90° vertical aiming
- Accommodates one glare control accessory
- Ceiling and wall mountable
- Remote power supply required (sold separately)
- 5 year warranty

SPECIFICATIONS

Input:	350mA 18V DC
Power:	6.5W
Light Source:	High output COB LED
Dimming:	Reference remote power supply specifications
Finish:	Electrostatically Powder Coated Black, White
Rated Life:	50,000 hours
Mounting:	Ceiling thickness of 1/2" - 1 1/2", Cut out of 1 3/4"
Standards:	ETL & cETL Damp Location listed, Title 24 JA8 Compliant

System	Model	CRI	Color Temp	Beam	Lumens	CBCP	Finish
MR Monopoint	2007	90	927 2700K	15°	155	1850	BK Black WT White
				50°	460	855	
			930 3000K	15°	160	1945	
				50°	485	900	
			935 3500K	15°	170	2045	
				50°	510	945	
			940 4000K	15°	175	2085	
				50°	520	960	

MR-2007- -

Example: MR-2007-930-BK

Accommodates one glare control accessory. Holder required sold separately.

ACCESSORY HOLDER

Black	LENS-S211-HLD-BK
White	LENS-S211-HLD-WT

GLARE CONTROL ACCESSORIES

Cross Louver	LENS-11P-CRL-BK LENS-11P-CRL-WT
Snoot	LENS-11-SNOOT-BK LENS-11-SNOOT-WT
Honeycomb	LENS-11-HCM

EXTENSIONS Custom order as a complete unit. Ceiling mount only.

X6 6"	MR2007	927 930 935 940	BK WT	
X12 12"				
X18 18"				
X24 24"				
X36 36"				
X48 48"				

Example: X12-MR2007930WT

wacighting.com
Phone (800) 526.2588
Fax (800) 526.2585

Headquarters, East Manufacturing Facility
44 Harbor Park Drive
Port Washington, NY 11050

South East Manufacturing Facility
1600 Distribution Ct
Lithia Springs, GA 30122

Central Manufacturing Facility
1700 South J Elmer Freeway, Ste 100
Cedar Hill, TX 75104



West Manufacturing Facility
1750 S Archibald Ave
Ontario, CA 91761

STEALTH SILO – MR-2007

Remote Driver Monopoint Luminaire

WAC

REMOTE POWER SUPPLY

		Model	Input	Output	Dimmable	L	W	H
	PS Power Supply	0350A-UR1	120V-277V	1 Channel, UL Class 2	100%-1% ELV, TRIAC, 0-10V	8¾"	2"	1½"
	PS Power Supply	0350A-UR6	120V-277V	6 Channel, UL Class 2	100%-1% ELV, TRIAC, 0-10V	10⅞"	3⅞"	1¼"

Example: **PS-0350A-UR6**

Home-run wiring. Recommended maximum distance between power supply and compatible light fixture is shown in below table:

	18 AWG	16 AWG	14 AWG	12 AWG
Maximum distance between power supply and light fixture	100 ft	150 ft	200 ft	250 ft

wacighting.com
Phone (800) 526.2588
Fax (800) 526.2585

Headquarters, East Manufacturing Facility
44 Harbor Park Drive
Port Washington, NY 11050

South East Manufacturing Facility
1600 Distribution Ct
Lithia Springs, GA 30122

Central Manufacturing Facility
1700 South J Elmer Freeway, Ste 100
Cedar Hill, TX 75104

West Manufacturing Facility
1750 S Archibald Ave
Ontario, CA 91761