


MT-4LD1 - 1 Light

4" LED Precision Multiples

WAC



Fixture Type:

Catalog Number:

Project:

Location:

PRODUCT DESCRIPTION

Retractable, adjustable spot lights

FEATURES

- ELV and 0-10V dimming options
- Invisible Trim™ is designed to sit flush with the ceiling for a clean, architectural look
- Fully retractable from housing
- 365° horizontal rotation and 180° vertical aiming
- Accepts 1 replacement lens
- 50,000 hour rated life
- 5 year WAC Lighting product warranty

SPECIFICATIONS

Construction: Die-cast aluminum heat sink painted black. Trim, housing and junction box are 20 gauge steel. Frame and hanger bars are heavy gauge galvanized steel.

J-Box: Seven knockouts and four Romex® style wiring connectors provided for ease of installation. Rated for branch wiring.

Driver: Universal (120V - 277V) or 120V input only

Light Source: High output LED (included with housing)

Dimming: 0-10V or ELV (see list of housings below)

Mounting: Supplied with hanger bars, adjustable from 9 1/4" - 24 1/2" to accommodate various joist construction and grid sizes. Hanger bars include a captive mounting "screw-nail" for ease of installation. Accommodates surface up to 1" thick. 5 1/8" x 5 1/8" cutout with trim, 5 1/8" x 5 1/8" cutout for Invisible Trim™. See instruction sheet for details on installation using spackle ring.

Finish: Abrasion resistant powder coat paint in Black (BK).

Standards: ETL & cETL Damp Location listed. Airtight.

TRIMS

		MT-4LD116T Trim	WT White BK Black
		MT-4LD116TL Invisible Trim™	WT White



HOUSINGS

	Power	Beam	Color Temp	CRI	Interior
	MT-4LD116N 0-10V dimming Non-IC, 120V-277V input	15W	S 20° F 40°	27	2700K 85
				927	2700K 90
	MT4LD116NE ELV dimming Non-IC, 120V input	15W	S 20° F 40°	30	3000K 85
				930	3000K 90
	MT4LD111NE ELV dimming IC-Rated, 120V input	11W	S 20° F 40°	35	3500K 85
				40	4000K 85



REPLACEMENT LENS

Amber	LENS-16-AMB	UV Filter	LENS-16-UVF
Blue	LENS-16-BLU	Frosted	LENS-16-FR
Green	LENS-16-GRN	Spread	LENS-16-SPR
Red	LENS-16-RED	Beam Elongator	LENS-16-BEL

wacighting.com

Phone (800) 526.2588

Fax (800) 526.2585

Headquarters, East Manufacturing Facility

44 Harbor Park Drive

Port Washington, NY 11050

South East Manufacturing Facility

1600 Distribution Ct

Lithia Springs, GA 30122

Central Manufacturing Facility

1700 South J Elmer Freeway, Ste 100

Cedar Hill, TX 75104

West Manufacturing Facility

1750 S Archibald Ave

Ontario, CA 91761

MT-4LD116 - 1 Light

4" LED Precision Multiples



LUMINAIRE PERFORMANCE	Power	Beam	Photometry	Color Temp	CRI	Lumen	CBCP	
MT-4LD116N 0-10V dimming Non-IC, 120V-277V input	15W	S 20°		27 2700K 85 1300 6990				REPLACEMENT HEADS (INCLUDES: ONE HEAD, LED, AND DRIVER) Housing Model Module MT-4LD116N 4MT4LD16N-S27-BK 4MT4LD16N-S30-BK 4MT4LD16N-S35-BK 4MT4LD16N-S40-BK 4MT4LD16N-S927-BK 4MT4LD16N-S930-BK 4MT4LD16N-F27-BK 4MT4LD16N-F30-BK 4MT4LD16N-F35-BK 4MT4LD16N-F40-BK 4MT4LD16N-F927-BK 4MT4LD16N-F930-BK MT4LD116NE 4MT4LD16NE-S27-BK 4MT4LD16NE-S30-BK 4MT4LD16NE-S35-BK 4MT4LD16NE-S40-BK 4MT4LD16NE-S927-BK 4MT4LD16NE-S930-BK 4MT4LD16NE-F27-BK 4MT4LD16NE-F30-BK 4MT4LD16NE-F35-BK 4MT4LD16NE-F40-BK 4MT4LD16NE-F927-BK 4MT4LD16NE-F930-BK MT4LD111NE 4MT4LD11NE-S27-BK 4MT4LD11NE-S30-BK 4MT4LD11NE-S35-BK 4MT4LD11NE-S40-BK 4MT4LD11NE-S927-BK 4MT4LD11NE-S930-BK 4MT4LD11NE-F27-BK 4MT4LD11NE-F30-BK 4MT4LD11NE-F35-BK 4MT4LD11NE-F40-BK 4MT4LD11NE-F927-BK 4MT4LD11NE-F930-BK
		F 40°		27 2700K 85 1265 3060				
		S 20°		27 2700K 85 1300 6990				
		F 40°		27 2700K 85 1265 3060				
MT4LD116NE ELV dimming Non-IC, 120V input	15W	S 20°		27 2700K 85 1300 6990				
		F 40°		27 2700K 85 1265 3060				
		S 20°		27 2700K 85 1030 5570				
		F 40°		27 2700K 85 1000 2395				
MT4LD111NE ELV dimming IC-Rated, 120V input	11W	S 20°		27 2700K 85 1030 5570				
		F 40°		27 2700K 85 1000 2395				
		S 20°		27 2700K 85 1030 5570				
		F 40°		27 2700K 85 1000 2395				

wacighting.com Headquarters, East Manufacturing Facility South East Manufacturing Facility Central Manufacturing Facility West Manufacturing Facility
 Phone (800) 526.2588 44 Harbor Park Drive 1600 Distribution Ct 1700 South J Elmer Freeway, Ste 100 1750 S Archibald Ave
 Fax (800) 526.2585 Port Washington, NY 11050 Lithia Springs, GA 30122 Cedar Hill, TX 75104 Ontario, CA 91761