



# MT-5LD125 - 1 Light

## Tesla LED Multiple Spots

# WAC LIGHTING

Responsible Lighting®



### PRODUCT DESCRIPTION

High brightness, retractable & adjustable spot light.

### FEATURES

- Non-IC rated, airtight housings
- Invisible Trim™ is designed to sit flush with the ceiling for a clean, architectural look
- Spot and Flood beam spreads
- 45° vertical adjustment and 365° horizontal rotation
- Accepts one replacement lens
- 50,000 hour rated life
- 5 year WAC Lighting product warranty

### FIXTURE PERFORMANCE

Model #	Beam	CCT	Watts	Lumens	Efficacy	CRI
MT-5LD125T-S927	25°	2700K	22.5W	1095	48.5 Lm/W	90
MT-5LD125T-F927	40°			1105	49 Lm/W	
MT-5LD125T-S27	25°	2700K	22.5W	1245	55 Lm/W	85
MT-5LD125T-F27	40°			1245	55 Lm/W	
MT-5LD125T-S930	25°	3000K	22.5W	1075	48 Lm/W	90
MT-5LD125T-F930	45°			1095	48.5 Lm/W	
MT-5LD125T-S30	25°	3000K	22.5W	1390	62 Lm/W	85
MT-5LD125T-F30	45°			1335	59 Lm/W	
MT-5LD125T-S35	25°	3500K	22.5W	1350	60 Lm/W	85
MT-5LD125T-F35	40°			1330	59 Lm/W	
MT-5LD125T-S40	25°	4000K	22.5W	1515	67 Lm/W	85
MT-5LD125T-F40	40°			1450	64 Lm/W	

### TRIM ORDER NUMBER

Model #	Beam	Color Temp	Rated	Finish
MT-5LD125T	Trim	<b>S</b> 25°	Non-IC	WT White
MT-5LD125TL	Invisible Trim™	<b>F</b> 40°		
		<b>927</b> 2700K (90 CRI)		
		<b>27</b> 2700K		
		<b>930</b> 3000K (90 CRI)		
		<b>30</b> 3000K		
		<b>35</b> 3500K		
		<b>40</b> 4000K		

Example:  -  -  - **WT**

Example: MT-5LD125T-S30-WT

### WAC Lighting

www.waclighting.com  
Phone (800) 526.2588 • Fax (800) 526.2585

### Headquarters/Eastern Distribution Center

44 Harbor Park Drive • Port Washington, NY 11050  
Phone (516) 515.5000 • Fax (516) 515.5050

### Western Distribution Center

1750 Archibald Avenue • Ontario, CA 91760  
Phone (800) 526.2588 • Fax (800) 526.2585

Fixture Type:

Catalog Number:

Project:

Location:

### SPECIFICATIONS

**Construction:** Die-cast aluminum heat sink painted white. Trim, housing and junction box are 20 gauge steel. Frame and hanger bars are heavy gauge galvanized steel.

**J-Box:** Seven knockouts and four Romex® style wiring connectors provided for ease of installation. Rated for branch wiring.

**Driver:** Universal Input (120V - 277V)

**Light Source:** High output LED

**Dimming:** Dim to 10% with electronic low voltage (ELV) dimmer (120V only). 0-10V dimming for 120V and 277V.

**Mounting:** Supplied with hanger bars, adjustable from 14½"-25" to accommodate various joist construction and grid sizes. Includes butterfly brackets which mount to ½" emt or channel and are vertically adjustable. 6½" x 6½" cutout with trim, 7¾" x 7¾" cutout for Invisible Trim™. See instruction sheet for details on installation using spackle ring. Accommodates surfaces from ½" to 1" thick.

**Finish:** Abrasion resistant powder coat paint in White (WT).

**Standards:** ETL & cETL Damp Location listed.

### COLOR LENSES LENSES

Color Lens	LENS-16
AMB	Amber
BLU	Blue
GRN	Green
RED	Red
YEL	Yellow

### LENSES

Clear Lens	
Frosted Lens	<b>LENS-16-CL</b>
Spread Lens	<b>LENS-16-FR</b>
Beam Soft Lens	<b>LENS-16-SPR</b>
Beam Elongating Lens	<b>LENS-16-BSL</b>
Infrared Filter Lens	<b>LENS-16-BEL</b>
UV/Infrared Filter Lens	<b>LENS-16-IR</b>
	<b>LENS-16-UI</b>

### ACCESSORIES

Honeycomb Louver	<b>LENS-16-HCM</b>
Cross Louver	<b>LENS-16-CRL</b>
2" Snoot	<b>LENS-16-SNOOT</b>

### HOUSING ORDER NUMBER

Non-IC Rated, Airtight New Construction

**MT-5LD125H-NA**

