R2FBNT-TW, R2FRNL-TW, R2FSNL-TW

FQ 2"Tunable White New Construction Housing





Fixture Type:

Catalog Number:

Project:

Location:

SPECIFICATIONS

Input Universal 120-277V AC 50/60 Hz

Standards: ETL & cETL, IC-rated, Airtight (see below for list)

Dimming: MyWAC App and WAC-Mesh WallStation: 100-0.1%

Mounting: New construction housings included with universal mounting

brackets and hanger bars


Ceiling cutout (Round and Square): Ø 3 1/2"

Ceiling thickness: ½" - 1 ¼"


Construction: 20 Gauge galvanized steel

Warranty: 5 year WAC Lighting product warranty

New Construction Trimmed



New Construction Trimless



HOUSINGS Model Power Rating

New Construction Trimmed	R2FBNT-TW	Round and Square	Airtight	1 2	14W 18W	IC IC
New Construction Trimless	R2FRNL-TW	Round (Spackle frame included)	Airtight	1 2	14W 18W	IC
	R2FSNL-TW	Square (Spackle frame included)	Airtight			IC

R2F -TW-

Example: R2FBNT-TW-1

waclighting.com Phone (800) 526.2588 Fax (800) 526.2585 **Headquarters, East Manufacturing Facility** 44 Harbor Park Drive Port Washington, NY 11050 South East Manufacturing Facility 1600 Distribution Ct Lithia Springs, GA 30122 **Central Manufacturing Facility** 1700 South J Elmer Freeway, Ste 100 Cedar Hill, TX 75104 West Manufacturing Facility 1750 S Archibald Ave Ontario, CA 91761

1

R2FBNT-TW, R2FRNL-TW, R2FSNL-TW

FQ 2"Tunable White New Construction Housing



REPLACEMENT DRIVER

Housing Model		ower	Replacement Driver Model		
R2FBNT-TW, R2FRNL-TW, R2FSNL-TW	1 2	14W 18W	D-R2FN-TW-1 D-R2FN-TW-2		