

R2FRAL-TWA

FQ 2" Tunable White - Round Adjustable Trimless



Fixture Type:

Catalog Number:

Project: _____

Location: _____

PRODUCT DESCRIPTION

FQ (Function + Quality) Experience simplicity and versatility with FQ 2" recessed luminaires. The fixtures merge modern design with world-class performance to achieve the ultimate in function and flexibility. Enjoy the benefits of two fixtures in one with Tunable White 1800-4000K and Dim-to-Warm 3000K-1800K features built into each luminaire, allowing you to customize the best light to illuminate dining areas, great rooms, primary bedrooms, kitchens, and baths on the fly. Deep regressed light sources deliver a glare-free, quiet ceiling aesthetic for a clean architectural look while providing up to 1250 lumens for robust output from a diminutive source.

FEATURES

- Two-piece die-cast construction
- Light engine mounted on trim with springs for easy replacement
- 0-35° vertical tilting and 365° horizontal rotation
- Center beam alignment retained throughout adjustment range
- Field changeable beam angle with reflectors provided
- Accepts one Lens or glare control accessory
- 5 year WAC Lighting product warranty

SPECIFICATIONS

Construction: Durable die-cast aluminum construction

Input: Universal 120-277V AC 50/60 Hz

Dimming: MyWAC App and WAC-Mesh WallStation: 100%-0.1%

Light Source: 3-step Mac Adam Ellipse Tunable White COB
Rated life of 50,000 hours at L70

Mounting: Heavy gauge retention clips support trim firmly.
Safety cabling standard.

Finish: Electrostatically powder coated White, Black, Dark Bronze. Enamel coated Haze.

Standards: ETL & cETL Damp Location Listed, Title 24 JA8 Compliant.

	Model	Beam	*Lumens	*CBCP	Color Temp	CRI	Finishes	Reflector/Trim
	R2FRAL Round Trimless	N 30°	980	2165	TWA 1800K - 4000K	90	BK DB HZ WT	Black Dark Bronze Haze White
		F 42°	915	1310				
		W 55°	920	1025				

R2FRAL-TWA-__

Example: **R2FRAL-TWA-BK** (Beam N-30° reflector is pre-installed. Beams F-42° and W-55° reflectors are included.)

* Lumens and CBCP are reference values for 3000K trim with 2 housing. Use multiplier table below to determine the output for other combinations.

LUMENS AND CBPC MULTIPLIER						
Housing Power Level	Color Temperature					
	1800K	2200K	2700K	3000K	3500K	4000K
1 (14W)	0.59	0.69	0.76	0.80	0.85	0.88
2 (18W)	0.74	0.86	0.95	1.00	1.06	1.10

Please see next page for housing units (required)

wacighting.com

Phone (800) 526.2588

Fax (800) 526.2585

Headquarters, East Manufacturing Facility

44 Harbor Park Drive

Port Washington, NY 11050

South East Manufacturing Facility

1600 Distribution Ct

Lithia Springs, GA 30122

Central Manufacturing Facility

1700 South J Elmer Freeway, Ste 100

Cedar Hill, TX 75104

West Manufacturing Facility

1750 S Archibald Ave

Ontario, CA 91761

R2FRAL-TWA

FQ 2" Tunable White - Round Adjustable Trimless



<i>HOUSING (Required)</i>		<i>Model</i>	<i>Power</i>
New Construction IC Airtight		R2FRNL-TW	1 14W IC 2 18W IC
Remodel Non-IC		R2FRRL-TW	1 14W Non-IC 2 18W Non-IC

R2FR__-TW-__

Example: R2FRNL-TW-2

GLARE CONTROL ACCESSORIES

LENS-11-HCM	<i>Honeycomb Louver</i>
LENS-11P-CRL-BK	<i>Cross Louver</i>

LENS ACCESSORIES

LENS-11	AMB	<i>Amber</i>
	RED	<i>Red</i>
	BLU	<i>Blue</i>
	GRN	<i>Green</i>
	SPR	<i>Spread</i>
	BEL	<i>Beam Elongating</i>

wacighting.com	Headquarters, East Manufacturing Facility	South East Manufacturing Facility	Central Manufacturing Facility	West Manufacturing Facility
Phone (800) 526.2588	44 Harbor Park Drive	1600 Distribution Ct	1700 South J Elmer Freeway, Ste 100	1750 S Archibald Ave
Fax (800) 526.2585	Port Washington, NY 11050	Lithia Springs, GA 30122	Cedar Hill, TX 75104	Ontario, CA 91761