

OCULARC 3.5

Wall Wash - R3CRWT, R3CRWL

WAC LIGHTING

Responsible Lighting®



Fixture Type:

Catalog Number:

Project:

Location:

PRODUCT DESCRIPTION

Ocularc 3.5 offers performance features in a simple but versatile package for residential and commercial applications alike. One housing can be used for downlight, adjustable, pinhole, wall wash trims.

FEATURES

- 3 beam angle options included: For Wall Wash trim optimal optics is light engine with no film installed.
- IC-Rated, Airtight, New Construction
- Adjustable LED light engine included with housing
- Shallow housing under 4" depth
- 5 year warranty

SPECIFICATIONS

Construction: Die-cast aluminum trim and heat sink

Dimming: 100% - 1% TRIAC, ELV
100% - 5%, 0-10V

Input Power: 13.5W, 120V-277V 50/60Hz

Light Source: High output COB LED rated life of 50,000 hours.

Mounting: Retention clips firmly hold trim to housing. Cutout 4¼"

Finish: Powder coated white, enamel-coated haze.

Ceiling thickness: ½" - 1"

Standards: UL & cUL, Wet location listed. Title 24 JA8-2016 Compliant

Operating Temperature: -4°F to 104°F (-20°C to 40°C)

Trims (Order Housing Separately)	Model	Beam	Color Temp	Lumens	CBCP	Finish
	R3CRWT Round Trim Wall Wash	Asymmetrical	927 2700K 930 3000K 935 3500K 940 4000K	590 635 650 680	N/A	HZWT Haze/White WT White BK Black
	R3CRWL Round Trimless Wall Wash	Asymmetrical	927 2700K 930 3000K 935 3500K 940 4000K	590 635 650 680	N/A	HZ Haze WT White BK Black

R3CRW__ -

Example: R3CRWT-WT

wacighting.com

Phone (800) 526.2588

Fax (800) 526.2585

Headquarters/Eastern Distribution Center

44 Harbor Park Drive

Port Washington, NY 11050

Central Distribution Center

1600 Distribution Ct

Lithia Springs, GA 30122

Western Distribution Center

1750 Archibald Avenue

Ontario, CA 91760

OCULARC 3.5

Wall Wash - R3CRWT, R3CRWL

WAC LIGHTING

Responsible Lighting®

Housing (Required) - Order separately from trims	Model	Power	Color Temp
	R3CRN-11 IC-Rated Airtight	13.5W	927 2700K 930 3000K 935 3500K 940 4000K
<p>Remodel Trim</p>	R3CRR-11 Non IC Airtight	13.5W	927 2700K 930 3000K
<p>Remodel Trimless</p>	R3CRRL-11 Non IC Airtight	13.5W	935 3500K 940 4000K

R3CR -11-

Example: R3CRN-11-927

FEATURES

- Adjustable LED light engine included with housing:
Optimal Vertical Adjustment for Wall Wash is 15° indexed position
- Trim or trimless with die-cast spackle frame included.
- Accepts one optional honeycomb louver or optical lens.

GLARE CONTROL ACCESSORIES sold separately

LENS-16	HCL	Honeycomb Louver
----------------	------------	------------------

LENS ACCESSORIES sold separately

LENS-16	AMB	Amber
	RED	Red
	FR	Frosted
	SPR	Spread
	BEL	Beam Elongating

wacighting.com

Phone (800) 526.2588

Fax (800) 526.2585

Headquarters/Eastern Distribution Center

44 Harbor Park Drive

Port Washington, NY 11050

Central Distribution Center

1600 Distribution Ct

Lithia Springs, GA 30122

Western Distribution Center

1750 Archibald Avenue

Ontario, CA 91760