

R4FSWL-TWA

FQ 4" Tunable White - Square Wall Wash Trimless



Fixture Type:

Catalog Number:

Project: _____

Location: _____

PRODUCT DESCRIPTION

FQ (Function + Quality) 4" recessed luminaires are simple and versatile. Combining modern design with world-class performance to achieve the ultimate function and flexibility, these fixtures feature Tunable White 1800-4000K technology built into each luminaire, allowing you to select the best white light to illuminate dining areas, great rooms, primary bedrooms, kitchens, and baths on the fly. Enjoy the benefits of two fixtures in one with Tunable White 1800-4000K and Dim-to-Warm 3000K-1800K features built into the luminaires, allowing you to customize the best light to illuminate dining areas, great rooms, primary bedrooms, kitchens, and baths on the fly. Deep regressed light sources deliver a glare-free, quiet ceiling aesthetic for a clean architectural look while deploying up to 1900 lumens for robust output.

FEATURES

- Two-piece die-cast construction
- Light engine mounted on trim with springs for easy replacement
- Designed for even wall illumination both vertically and horizontally
- 5 year WAC Lighting product warranty

SPECIFICATIONS

- Construction:** Durable die-cast aluminum construction
- Input:** Universal 120-277V AC 50/60 Hz
- Dimming:** MyWAC App and WAC-Mesh WallStation: 100-0.1%
- Light Source:** 3-step Mac Adam Ellipse Tunable White COB
Rated life of 50,000 hours at L70
- Mounting:** Heavy gauge retention clips support trim firmly. Safety cabling standard.
- Finish:** Electrostatically powder coated White, Black, Dark Bronze. Enamel coated Haze.
- Standards:** ETL & cETL Wet Location Listed

	Model	Beam	*Lumens	CBCP	Color Temp	CRI	Finishes	Reflector/Trim
	R4FSWL Square Trimless	A Asym	1080	N/A	TWA 1800K - 4000K	90	BK DB HZ WT	Black Dark Bronze Haze White

R4FSWL-TWA-__

Example: **R4FSWL-TWA-WT**

*Lumens shown in the table are reference values for 3000K trim with 3 housing. Use multiplier table below to determine the output for other combinations.

LUMENS AND CBPC MULTIPLIER						
Housing Power Level	Color Temperature					
	1800K	2200K	2700K	3000K	3500K	4000K
1 (14W)	0.42	0.48	0.53	0.56	0.59	0.63
2 (19W)	0.59	0.67	0.74	0.78	0.83	0.88
3 (26W)	0.76	0.86	0.95	1.00	1.07	1.13

Please see next page for housing units (required)

wacighting.com	Headquarters, East Manufacturing Facility	South East Manufacturing Facility	Central Manufacturing Facility	West Manufacturing Facility
Phone (800) 526.2588	44 Harbor Park Drive	1600 Distribution Ct	1700 South J Elmer Freeway, Ste 100	1750 S Archibald Ave
Fax (800) 526.2585	Port Washington, NY 11050	Lithia Springs, GA 30122	Cedar Hill, TX 75104	Ontario, CA 91761

R4FSWL-TWA

FQ 4" Tunable White - Square Wall Wash Trimless



HOUSING (Required)		Model	Power
<p>New Construction IC Airtight</p>		<p>R4FSNL-TW</p>	<p>1 14W IC 2 19W IC 3 26W IC</p>
<p>Remodel Non-IC</p>		<p>R4FSRL-TW</p>	<p>1 14W Non-IC 2 19W Non-IC 3 26W Non-IC</p>

R4FS__-TW-__

Example: R4FSNL-TW-1