

R4RD2T, R4SD2T

4.5" Volta Tunable White - Downlight Trim

WAC




PRODUCT DESCRIPTION

Volta 4.5" Tunable White recessed series represents an innovation in design and technology for architectural lighting. This high lumen and adaptable family of fixtures with a comprehensive set of round and square fittings, affords a sustainable solution for commercial, corporate, and upscale residential applications.

FEATURES

- Natural and Vivid Precision LED CCT Tuning
- 2" lens regress for superior glare control
- Field selectable light engine height for cut-off angle adjustment (30°-34°) and accessory use
- Integral patterned tempered trim lens included standard
- Compatible with wide range of accessories
- 5 year warranty



R4RD2T Round Trim
R4SD2T Square Trim

Fixture Type:

Catalog Number:

Project:

Location:

SPECIFICATIONS

Construction: Durable die-cast self flanged aluminum construction

Input: Universal 120-277V AC 50/60 Hz

Dimming: 2 Channel 0-10V: 100-0.1%
2 Channel DMX512-A, with RDM: 100-0.1%
Linear Dimming. 1st input channel is intensity changing.
2nd input channel is CCT changing.

Light Source: High output 3-step Mac Adam Ellipse COB
Rated life of 50,000 hours at L70

Mounting: Heavy gauge retention clips support trim firmly.
Safety cabling standard.
Ceiling cut out (Round): Ø5 1/8"
Ceiling cut out (Square): 5 1/8" x 5 1/8"
Accommodates 1/2" - 1 1/2" ceiling thickness

Finish: Electrostatically powder coated White, Black.
Enamel coated Haze. Plated and brushed copper Bronze.

Standards: ETL & cETL Wet location listed, Title 24 JA8 Compliant

TRIM	Model	Beam	Lumens	CBCP	Ref Output*	Color Temp	CRI	Finishes	Reflector/Trim
		N 25°	Round	2295	6420				
			Square	2445	6835				
		F 45°	Round	2185	3600				
			Square	2315	3805				
		W 60°	Round	2215	2460				
			Square	2345	2600				
		N 25°	Round	2520	6915				
			Square	2680	7365				
		F 45°	Round	2495	3990				
			Square	2640	4220				
		W 60°	Round	2565	2730				
			Square	2715	2890				
					TWA 1800K-4000K	98			
					TWB 2700K-6500K	98			
								BK	Black
								BKWT	Black/White
								CB	Copper Bronze
								HZ	Haze
								HZWT	Haze/White
								WT	White

Example: **R4SD2T-NTWA-WT**

*Reference output shows TWA/TWB trim tuned to 3000K with **36** housing. Use multiplier table below to determine the output for other combinations

Lumens & CBCP Multiplier		Color Temperature					
	Housing Power Level	1800K	2200K	2700K	3000K	3500K	4000K
TWA (1800K-4000K)	36 (44W)	0.68	0.82	0.94	1.00	1.07	1.11
	25 (29W)	0.48	0.57	0.66	0.70	0.75	0.78
	15 (20W)	0.33	0.39	0.45	0.48	0.51	0.53
TWB (2700K-6500K)	Housing Power Level	2700K	3000K	3500K	4000K	5000K	6500K
	36 (44W)	0.96	1.00	1.06	1.09	1.12	1.11
	25 (29W)	0.67	0.70	0.74	0.76	0.78	0.78
	15 (20W)	0.46	0.48	0.51	0.52	0.54	0.53

Example: **R4SD2T-NTWA-WT** turned to 4000K with **36** housing: 2445 lm (Reference Output) x 1.11 (Multiplier) = 2714 lm
6835 CBCP (Reference Output) x 1.11 (Multiplier) = 7587 CBCP

Please see next page for housing, power supply and tool units (required)

waclighting.com	Headquarters, East Manufacturing Facility	South East Manufacturing Facility	Central Manufacturing Facility	West Manufacturing Facility
Phone (800) 526.2588	44 Harbor Park Drive	1600 Distribution Ct	1700 South J Elmer Freeway, Ste 100	1750 S Archibald Ave
Fax (800) 526.2585	Port Washington, NY 11050	Lithia Springs, GA 30122	Cedar Hill, TX 75104	Ontario, CA 91761

R4RD2T, R4SD2T

4.5" Volta Tunable White - Downlight Trim

WAC

HOUSING (Required)	Model	Power	Rating	Driver
Round New Construction	R4RNT Airtight	15 20W 25 29W 36 44W	IC rated IC rated Non-IC	T-X DMX512-A T-Z 2CH 0-10V
Square New Construction	R4SNT Airtight	15 20W 25 29W 36 44W	IC rated IC rated Non-IC	T-X DMX512-A T-Z 2CH 0-10V
Remodel	R4BRT Round & Square	15 20W 25 29W 36 44W	Non-IC Non-IC Non-IC	T-X DMX512-A T-Z 2CH 0-10V

Example: **R4RNT-15T-X**

Field Replaceable Driver

D-R4N-15T-X DMX512-A Driver for 20W New Const. Housing
D-R4N-25T-X DMX512-A Driver for 29W New Const. Housing
D-R4N-36T-X DMX512-A Driver for 44W New Const. Housing

D-R4N-15T-Z 2CH 0-10V Driver for 20W New Const. Housing
D-R4N-25T-Z 2CH 0-10V Driver for 29W New Const. Housing
D-R4N-36T-Z 2CH 0-10V Driver for 44W New Const. Housing

FIELD CHANGEABLE GLARE CONTROL AND OPTIC SYSTEM




Accessory holder

LENS-73-HLD Required to hold lens and glare control accessories

Glare control accessories

LENS-73-HCL Honeycomb Louver
LENS-73-CRL Cross Louver

Optical cartridge
Allows tool-less exchange of reflectors



Reflector
For narrow flood, flood, and wide flood.

Interchangeable reflector

REF-R4-N Narrow Flood beam reflector
REF-R4-F Flood beam reflector
REF-R4-W Wide beam reflector

waclighting.com

Phone (800) 526.2588

Fax (800) 526.2585

Headquarters, East Manufacturing Facility

44 Harbor Park Drive

Port Washington, NY 11050

South East Manufacturing Facility

1600 Distribution Ct

Lithia Springs, GA 30122

Central Manufacturing Facility

1700 South J Elmer Freeway, Ste 100

Cedar Hill, TX 75104

West Manufacturing Facility

1750 S Archibald Ave

Ontario, CA 91761

NATURAL TUNABLE WHITE CCT TUNING:

The CCT of the Volta Tunable White fixture may be adjusted.

Using the DMX byte values in the adjacent table mapped to CH1 and CH2 of the desired output, increments of 100K (Kelvin) from 1800K to 4000K for TWA and 2700K to 6500K for TWB, at full intensity.

Note: Through compatible RDM tool, fixture channels can be reassigned to desired consecutive channels. Factory default is DMX channel 1 and 2.

VOLTA 4.5" TUNABLE WHITE DMX BYTE VALUE VS CCT**TWA DMX
BYTE VALUES AT FULL INTENSITY**

CCT (K)	CH1: Intensity	CH2: CCT
4000	255	255
3900	255	250
3800	255	240
3700	255	230
3600	255	219
3500	255	207
3400	255	196
3300	255	186
3200	255	176
3100	255	163
3000	255	153
2900	255	140
2800	255	130
2700	255	117
2600	255	105
2500	255	92
2400	255	79
2300	255	66
2200	255	51
2100	255	38
2000	255	23
1900	255	10
1800	255	0

**TWB DMX
BYTE VALUES AT FULL INTENSITY**

CCT (K)	CH1: Intensity	CH2: CCT
6500	255	252
6400	255	249
6300	255	245
6200	255	243
6100	255	241
6000	255	237
5900	255	234
5800	255	230
5700	255	226
5600	255	222
5500	255	218
5400	255	214
5300	255	210
5200	255	205
5100	255	200
5000	255	195
4900	255	190
4800	255	185
4700	255	180
4600	255	175
4500	255	170
4400	255	164
4300	255	158
4200	255	151
4100	255	143
4000	255	134
3900	255	125
3800	255	119
3700	255	110
3600	255	101
3500	255	92
3400	255	83
3300	255	74
3200	255	64
3100	255	53
3000	255	41
2900	255	29
2800	255	15
2700	255	0