DOUBLE ADJUSTABLE FLOOD LIGHT

Endurance™ - WP-LED529

WAC LIGHTING
Responsible Lighting®

Fixture Type:

Catalog Number:

Project:

Location:



PRODUCT DESCRIPTION

Die cast aluminum factory sealed luminaire with patent pending design for a water and dust proof IP66 rated outdoor.

FEATURES

- Rotate to continuously adjust beam angles indexed at 15°, 25°, 40°, 60°
- IP66 and ETL & cETL Wet Location Listed
- Factory-Sealed LED Light Engine
- Die-Cast Aluminum Construction
- 120V Direct Wire - No Driver Needed
- Safety cable and canopy included
- Comes with extension rod kit to extend up to 44" total
- Detachable Shroud
- Safety cable recommended for extensions over 36"
- One 6", one 12", one 24" field interchangable rods included

SPECIFICATIONS

Construction: Die-cast aluminum

Power: Line Voltage input (120V)

CRI: 85

Dimming: 100% - 10% with Electronic Low Voltage (ELV) dimmer

Finish: Architectural Bronze, Black, Graphite and White

Operating Temp: -40˚F to 122˚F (-40˚C to 50˚C)

Standards: IP66, Wet Location, ETL & cETL Listed

Rated Life: 50,000 hours

ORDER NUMBER

	Power	*Comparable*	*Beam*	*Delivered Lumens*	*CBCP*	*Color Temp*		*Finish*	
WP-LED529 *Double*	*30W*	*150W x2 PAR38*	*15˚ 60˚*	*600 x2 985 x 2*	*4145 x 2 875 x 2*	**30**	*3000K*	**ABZ**	*Architectural Bronze*
								ABK	*Architectural Black*
								AGH	*Architectural Graphite*
			15˚ 60˚	*695 x 2 1140 x 2*	*4800 x 2 1015 x 2*	**40**	*4000K*	**AWT**	*Architectural White*

Example: **WP-LED529-30-ABZ**

WAC Lighting
www.waclighting.com
Phone (800) 526.2588 • Fax (800) 526.2585

Headquarters/Eastern Distribution Center
44 Harbor Park Drive • Port Washington, NY 11050
Phone (516) 515.5000 • Fax (516) 515.5050

Western Distribution Center
1750 Archibald Avenue • Ontario, CA 91760
Phone (800) 526.2588 • Fax (800) 526.2585

WAC Lighting retains the right to modify the design of our products at any time as part of the company's continuous improvement program. FEB 2017